

TCR ADVANCED SL 1 (AXS)

GIANT



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Dark Chrome/Iris
RAMME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
STYRSTEM	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SETEPINNE	Giant Integrated Seatpost, -5/+15mm offset
SADEL	Giant Fleet SLR
DRIVVERK	
GIRHENDLER	SRAM Force AXS E1
FRONTGIR	SRAM Force AXS E1
BAKGIR	SRAM Force AXS E1
BREMSE	SRAM Force AXS E1 hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
BREMSEHENDLER	SRAM Force AXS E1
KASSETT	SRAM Force E1, 12-speed, 10x36
KJEDE	SRAM Force E1
KRANK	SRAM Force AXS E1, 33/46 with SRAM power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EIKE	Giant Aero Carbon Spoke
DEKK	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

Alle spesifikasjonene kan endres uten varsel.