

TCR ADVANCED SL 1 AXS

GIANT



產品規格

車架	
尺寸	XS, S, M, M/L, L
顏色	Blue Dragonfly / Iris 飛翔藍
車架	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
前叉	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	Giant Contact SLR XS:37/40cm, S:37/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm,
把手帶/套	Stratus Lite 2.0
握桿	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm,
座桿	Giant Integrated Seatpost, -5/+15mm offset
坐墊	Giant Fleet SLR
踏板	N/A
DRIVETRAIN	
變速把手	SRAM Force AXS
前變速器	SRAM Force AXS
後變速器	SRAM Force AXS
煞車系統	SRAM Force eTap hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
煞車把手	SRAM Force AXS
飛輪	SRAM Force, 12-speed, 10x36
鍊條	SRAM Force D1
大齒盤	SRAM Force AXS, 33/46 with SRAM power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
輻條	Giant Aero Carbon Spoke
外胎	CADEX Race, tubeless, 700x28c, folding
其他	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Price: NT\$238,000

車架幾何

車架	XS	S	M	ML	L	XL
座(立)管長 (mm)	680	710	740	770	800	830
座(立)管角度	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
上管長度 (mm)	520	535	550	565	580	600
頭管長度 (mm)	120	130	145	165	185	200
頭管角度	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
前叉 (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
前後輪距 (mm)	976	977	980	991	1006	1020
後下叉長度 (mm)	405	405	405	405	405	405
五通下降高度 (mm)	72	69.5	69.5	67	67	67
頭碗至五通高度 (mm)	517	528	545	562	581	596
頭碗至五通長度 (mm)	376	383	388	393	402	412
上管至地面高度 (mm)	703	722	743	771	798	822
把手寬 (mm)	400	400	420	420	440	440
龍頭長度 (mm)	80	90	100	110	110	120
曲柄長度 (mm)	170	170	172.5	172.5	175	175
輪組尺寸	700C	700C	700C	700C	700C	700C

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。