

TCR ADVANCED SL 1*

GIANT



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | XS, S, M, M/L, L, XL |
| COLORS | Dark Chrome |
| FRAME | Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc |
| FORK | Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR XS:37/42cm, S:37/42cm, M:39/44cm, M/L:39/44cm, L:39/44cm, XL:39/44cm |
| GRIPS | Stratus Lite 2.0 |
| STEM | Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| SEATPOST | Advanced SL-Grade composite, integrated design, -5/+15mm offset |
| SADDLE | Giant Fleet SLR |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | Shimano Ultegra Di2 ST-R8170 |
| FRONT DERAILLEUR | Shimano Ultegra Di2 FD-R8150 |
| REAR DERAILLEUR | Shimano Ultegra Di2 RD-R8150 |
| BRAKES | Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm |
| BRAKE LEVERS | Shimano Ultegra Di2 hydraulic |
| CASSETTE | Shimano Ultegra, 12-speed, 11x34 |
| CHAIN | Shimano Ultegra, CN-M8100 |
| CRANKSET | Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|---------------------------|---|
| RIMS | Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm |
| HUBS | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | Giant Aero Carbon Spoke |
| TIRES | CADEX Race GC, tubeless, 700x30c (30mm), folding |
| EXTRAS | Computer mount, tubeless prepared, 33mm max tyre size |
| LIMITS | |
| MAX TIRE CLEARANCE | 33 mm |

Price: \$9,999.00

GEOMETRY

| FRAME | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 680 | 710 | 740 | 770 | 800 | 830 |
| Seat Tube Angle | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Head Tube Length (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Head Tube Angle | 71.0° | 72.3° | 73.0° | 73.0° | 73.0° | 73.0° |
| Fork Rake (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 72.1 | 64 | 59.2 | 59.2 | 59.2 | 59.2 |
| Wheelbase (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 70 | 70 | 67 | 67 | 67 |
| Stack (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Reach (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Stand Over Height (mm) | 719 | 734 | 752 | 768 | 786 | 803 |
| Stem Length (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Crank Length (mm) | 165 | 165 | 170 | 170 | 172.5 | 172.5 |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.