

TCR ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Blue Dragonfly / Iris
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite D-shaped OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR, composite, 11-degree flare
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SLR Aerolight, -10-degree
SEATPOST	Giant Integrated Seatpost, -5/+15mm offset
SADDLE	Giant Fleet SLR
PEDALS	N/A
HEADSET	N/A
ARM REST KIT	N/A
EXTENSION BARS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2, 2x12
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra hydraulic Shimano RT-CL800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano Ultegra, CN-M8100
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter
BOTTOM BRACKET	Shimano BB71, press fit

WHEELS	
RIMS	Giant SLR 0 40 Carbon Disc WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TIRES	CADEX Race GC, tubeless, 700x28c (28mm), 120 TPI, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm max tire size

Suggested Retail Price (CDN): \$9,999.00

FRAME GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.