



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Dark Chrome/Iris
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact SLR XS:420/370mm, S:420/370mm, M:440/390mm, M/L:440/390mm, L:440/390mm, XL:440/390mm
GRIPS	Stratus Lite 2.0
STEM	Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SEATPOST	Giant Integrated Seatpost, -5/+15mm offset
SADDLE	Giant Fleet SLR
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano CN-M8100
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm, M/L:170mm, L:172.5mm, XL:172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TIRES	CADEX Road Race GC, tubeless, 700x30mm, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	420	420	440	440	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.