



SPECIFIKACIJE

| OKVIR | |
|---------------------|--|
| VELIKOSTI | XS, S, M, M/L, L, XL |
| BARVE | Blue Dragonfly / Iris |
| OKVIR | Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc |
| VILICE | Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| KOMPONENTE | |
| KRMILO | Giant Contact SLR XS:39/40cm, S:39/40cm, M:39/42cm, M/L:39/42cm, L:41/44cm, XL:41/44cm |
| GRIPS | Stratus Lite 2.0 |
| OPORA KRMILA | Giant Contact SLR AeroLight XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm |
| OPORA SEDEŽA | Giant Integrated Seatpost, -5/+15mm offset |
| SEDEŽ | Giant Fleet SLR |
| PEDALA | N/A |
| POGON | |
| PRESTAVNE ROČICE | Shimano Ultegra Di2 |
| PREDNJI MENJALNIK | Shimano Ultegra Di2 FD-R8150 |
| ZADNJI MENJALNIK | Shimano Ultegra Di2 RD-R8150 |
| ZAVORE | Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm |
| ZAVORNE ROČICE | Shimano Ultegra Di2 |
| VERIŽNIK | Shimano Ultegra, 12-speed, 11x34 |
| VERIGA | Shimano CN-M8100 |
| GONILKE Z VERIŽNIKI | Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Shimano, press fit |

| OBROČNIKI | |
|--------------------|---|
| OBROČI | Giant SLR 0 40 WheelSystem, [F]40mm, [R]40mm |
| PESTA | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| NAPERE | Giant Aero Carbon Spoke |
| PLAŠČI | CADEX Race GC, tubeless, 700x28c (28mm), folding |
| DODATKI | computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 33mm |

GEOMETRIJA

| OKVIR | XS | S | M | ML | L | XL |
|--|-------|-------|-------|-------|-------|-------|
| Dolžina sedežne cevi (mm) | 680 | 710 | 740 | 770 | 800 | 830 |
| Kot sedežne cevi | 74,5° | 74,0° | 73,5° | 73,0° | 73,0° | 72,5° |
| Top Tube Length (mm) | 520 | 535 | 550 | 565 | 580 | 600 |
| Višina glave okvirja (mm) | 120 | 130 | 145 | 165 | 185 | 200 |
| Krmlini kot | 71,0° | 72,3° | 73,0° | 73,0° | 73,0° | 73,0° |
| Zamik vpetja osi (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 72 | 64 | 59 | 59 | 59 | 59 |
| Medosna razdalja (mm) | 976 | 977 | 980 | 991 | 1006 | 1020 |
| Dolžina cevi ob verigi (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 69,5 | 69,5 | 67 | 67 | 67 |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 517 | 528 | 545 | 562 | 581 | 596 |
| Doseg (mm) | 376 | 383 | 388 | 393 | 402 | 412 |
| Višina zgornje cevi (mm) | 703 | 722 | 743 | 771 | 798 | 822 |
| Širina krmila (mm) | 400 | 400 | 420 | 420 | 440 | 440 |
| Dolžina opore krmila (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Dolžina gonilke (mm) | 170 | 170 | 172,5 | 172,5 | 175 | 175 |
| Velikost obročnikov | 700C | 700C | 700C | 700C | 700C | 700C |

Vse navedene specifikacije se lahko spremenijo brez obvestila.