

# TCR ADVANCED SL DISC 0



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Raw Carbon
<b>FRAME</b>	Advanced SL-grade composite, integrated seatpost, disc
<b>FORK</b>	Advanced SL-grade composite, full-composite OverDrive 2 steerer, disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
<b>GRIPS</b>	Stratus Lite 2.0
<b>STEM</b>	Giant Contact SLR XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
<b>SEATPOST</b>	Advanced SL-grade composite, integrated design, -5/+15mm offset
<b>SADDLE</b>	Giant Fleet SLR
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Dura-Ace Di2 ST-R9270
<b>FRONT DERAILLEUR</b>	Shimano Dura-Ace Di2 ST-R9250
<b>REAR DERAILLEUR</b>	Shimano Dura-Ace Di2 ST-R9250
<b>BRAKES</b>	Shimano Dura-Ace Di2 hydraulic, Shimano RT-CL900 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano Dura-Ace Di2 hydraulic
<b>CASSETTE</b>	Shimano Dura-Ace, 12-speed, 11x34
<b>CHAIN</b>	Shimano Dura-Ace M9100
<b>CRANKSET</b>	Shimano Dura-Ace, 36/52 with FC-9200P power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	CADEX 36 Disc WheelSystem, [F] 36mm, [R] 36mm
<b>HUBS</b>	[F] CADEX R1 Hub, CenterLock, 12mm thru-axle [R] CADEX R1-C30 Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	CADEX Aero Carbon
<b>TIRES</b>	CADEX Race, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	Computer mount, tubeless prepared, 32mm max tyre size

**Price: \$12,999.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	706	725	747	773	800	816
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.