

TCR ADVANCED SL DISC 0 RED



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Raw Carbon/Iris / Reflective Silver
CUADRO	Advanced SL-Grade Composite, integrated seatpost, disc
TIJERA	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
AMORTIGUADOR	N/A
COMPONENTES	
MANUBRIO	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
POTENCIA	Giant Contact SLR XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
POSTE DE ASIENTO	Advanced SL-Grade composite, integrated design, -5/+15mm offset
ASIENTO	Giant Fleet SLR
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM RED eTap AXS
DESVIADOR	SRAM RED eTap AXS
CAMBIO TRASERO	SRAM RED eTap AXS
FRENOS	SRAM RED eTap AXS hydraulic, SRAM CenterLine XR rotors [F]160mm, [R]140mm
PALANCAS DE FRENOS	SRAM RED eTap AXS hydraulic
CASSETTE	SRAM RED, 12-speed, 10x33
CADENA	SRAM RED D1
MULTIPLICACIÓN	SRAM RED D1 DUB, 35/48with Quarq DZero power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	CADEX 42 Disc WheelSystem
MAZAS	CADEX 42 Disc WheelSystem, 12mm thru-axle
RAYOS	CADEX 42 Disc WheelSystem
NEUMÁTICOS	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, tubeless prepared, 32mm max tire size

Precio: \$289,900.00

GEOMETRÍA

CUADRO	XS	S	M	ML	L	XL
Longitud de la Base del Poste de Asiento (mm)	680	710	740	770	800	830
Ángulo de la Base del Poste de Asiento	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Longitud del Tubo Superior (mm)	520	535	550	565	580	600
Longitud del Telescopio (mm)	120	130	145	165	185	200
Ángulo del Telescopio	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Rake (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Distancia entre Ejes (mm)	976	977	980	991	1006	1020
Longitud de Vaina Inferior (mm)	405	405	405	405	405	405
Caída del Eje de Centro (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Altura del Tubo Superior al Suelo (mm)	706	725	747	773	800	816
Ancho del Manubrio (mm)	400	400	420	420	440	440
Longitud de la Potencia (mm)	80	90	100	110	110	120
Longitud de la Biela (mm)	170	170	172.5	172.5	175	175
Tamaño de las Ruedas	700C	700C	700C	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.