



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
BARVE	Matte Raw Carbon/Gloss Rainbow Lightning
OKVIR	Advanced SL-Grade Composite, integrated seatpost, disc
VILICE	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
OPORA KRMILA	Giant Contact SLR XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
OPORA SEDEŽA	Advanced SL-Grade composite, integrated design, -5/+15mm offset
SEDEŽ	Giant Fleet SLR
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Dura-Ace Di2 ST-R9270
PREDNJI MENJALNIK	Shimano Dura-Ace Di2 ST-R9250
ZADNJI MENJALNIK	Shimano Dura-Ace Di2 ST-R9250
ZAVORE	Shimano Dura-Ace Di2 hydraulic, Shimano RT-MT900 rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano Dura-Ace Di2 hydraulic
VERIŽNIK	Shimano Dura-Ace, 12-speed, 11x34
VERIGA	Shimano Dura-Ace M9100
GONILKE Z VERIŽNIKI	Shimano Dura-Ace, 36/52 with FC-9200P power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	CADEX 36 Disc WheelSystem, [F] 36mm, [R] 36mm
PESTA	[F] CADEX Low Friction Hub, CenterLock, 12mm thru-axle, [R] CADEX R1-C30 Hub, CenterLock, 12mm thru-axle
NAPERE	CADEX Aero Carbon
PLAŠČI	CADEX Race, tubeless, 700x25c (26.5mm), folding
DODATKI	computer mount, tubeless prepared, 32mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	680	710	740	770	800	830
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	706	725	747	773	800	816
Širina krmila (mm)	400	400	420	420	440	440
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	170	170	172,5	172,5	175	175
Velikost obročnikov	700C	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.