

# TCR ADVANCED SL FRAMESET



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, M/L, L, XL
<b>COLOURS</b>	Opal, Raw Carbon, Psychedelic Green, Maraya Blue
<b>FRAME</b>	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>SEATPOST</b>	Advanced SL-Grade composite, integrated design, -5/+15mm offset
DRIVETRAIN	
<b>BOTTOM BRACKET</b>	BB86 accepts press fit style BB only, bearing set not included

WHEELS	
<b>EXTRAS</b>	Front & rear 12mm thru-axes, 20mm & 45mm ISP clamps
LIMITS	
<b>MAX TYRE CLEARANCE</b>	33mm

**Price: \$5,299.00**

## GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72	64	59	59	59	59
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	703	722	743	771	798	822
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172.5	172.5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

*Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.*