TCR ADVANCED SL FRAMESET

SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLORS	Sincity
FRAME	Advanced SL-Grade Composite, integrated seatpost
FORK	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer
SHOCK	N/A
COMPONENTS	
SEATPOST	Advanced SL-Grade composite, integrated design, -5/+15mm offset

WHEELS	
EXTRAS	28mm max tire size, 12mm thru-axles

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	680	710	740	770	800	830
Seat Tube Angle	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	702	722	743	769	793	813
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.