

TCR ADVANCED SL TEAM FRAMESET



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Purple Storm
FRAME	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
SEATPOST	Giant Integrated Seatpost, -5/+15mm offset

WHEELS	
EXTRAS	computer mount, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Suggested Retail Price (CDN): \$4,799.00

FRAME GEOMETRY

FRAME	XS	S	M	ML	L
Seat Tube Length (mm)	680	710	740	770	800
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	520	535	550	565	580
Head Tube Length (mm)	120	130	145	165	185
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	72	64	59	59	59
Wheelbase (mm)	976	977	980	991	1006
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	67	67
Stack (mm)	517	528	545	562	581
Reach (mm)	376	383	388	393	402
Stand Over Height (mm)	703	722	743	771	798
Handlebar Width (mm)	400	400	420	420	440
Stem Length (mm)	80	90	100	110	110
Crank Length (mm)	170	170	172.5	172.5	175
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.