

TCR ADVANCED-UI2



SPECS

FRAME	
SIZES	XS, S, M, M/L, L, XL
COLOURS	Arctic Light
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant Contact, 31.8mm, Reach 68mm & Drop 120mm (360-380mm), Reach 72mm & Drop 125mm (400-440mm) XS: 380mm, S: 380mm, M: 400mm, M/L: 400mm, L: 420mm, XL: 420mm
GRIPS	Stratus Lite 2.0 w/ gel
STEM	Giant Contact Aerolight, -10° XS: 80mm, S: 90mm, M: 100mm, M/L: 110mm, L: 110mm, XL: 120mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Giant Approach, 7mm steel rail, with LiniClip / ParticleFlow technology
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 HRD
FRONT DERAILLEUR	Shimano Ultegra Di2
REAR DERAILLEUR	Shimano Ultegra Di2
BRAKES	Shimano Ultegra Di2 HRD hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
BRAKE LEVERS	Shimano Ultegra Di2 HRD
CASSETTE	Shimano CS-R8100, 11x34
CHAIN	Shimano CN-M8100, 12-speed
CRANKSET	Shimano Ultegra, 30/51 XS: 165mm, S: 165mm, M: 170mm, M/L: 170mm, L: 172.5mm, XL: 172.5mm
BOTTOM BRACKET	Shimano, press fit 71

WHEELS	
RIMS	Giant SLR 2 40 Carbon Disc WheelSystem
HUBS	Giant SLR 2 40 WheelSystem hubs (integrated)
TYRES	Giant Gavia Course 0 tubeless, 700x30c, 170 TPI, folding
LIMITS	
MAX TIRE CLEARANCE	700x33mm

Price: €4,798.80

GEOMETRY

FRAME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	425	445	470	500	530	560
Seat Tube Angle	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Top Tube Length (mm)	520	535	550	565	580	600
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Wheelbase (mm)	976	977	980	991	1006	1020
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Stand Over Height (mm)	719	734	752	768	786	803
Handlebar Width (mm)	380	380	400	400	420	420
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	165	165	170	170	172.5	172.5

All specifications listed are subject to change without notice.