

TCR ADVANCED-UI2



SPECS

QUADRO	
TAMANHOS	XS, S, M, M/L, L, XL
QUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	Giant Contact, 31.8mm, Reach 68mm & Drop 120mm (360-380mm), Reach 72mm & Drop 125mm (400-440mm) XS: 380mm, S: 380mm, M: 400mm, M/L: 400mm, L: 420mm, XL: 420mm
PUNHOS	Stratus Lite 2.0 w/ gel
AVANÇO	Giant Contact Aerolight, -10° XS: 80mm, S: 90mm, M: 100mm, M/L: 110mm, L: 110mm, XL: 120mm
ESPIGÃO DE SELIM	Giant Variant, composite, -5/+15mm offset
SELIM	Giant Approach, 7mm steel rail, with LiniClip / ParticleFlow technology
TRANSMISSÃO	
MANETES	Shimano Ultegra Di2 HRD
DESVIADOR DIANTEIRO	Shimano Ultegra Di2
DESVIADOR TRASEIRO	Shimano Ultegra Di2
TRAVÕES	Shimano Ultegra Di2 HRD hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
MANÍPULOS DOS TRAVÕES	Shimano Ultegra Di2 HRD
CASSETE	Shimano CS-R8100, 11x34
CORRENTE	Shimano CN-M8100, 12-speed
CONJUNTO PEDALEIRO	Shimano Ultegra, 30/51 XS: 165mm, S: 165mm, M: 170mm, M/L: 170mm, L: 172.5mm, XL: 172.5mm
MOVIMENTO CENTRAL	Shimano, press fit 71

RODAS	
AROS	Giant SLR 2 40 Carbon Disc WheelSystem
CUBOS	Giant SLR 2 40 WheelSystem hubs (integrated)
PNEUS	Giant Gavia Course 0 tubeless, 700x30c, 170 TPI, folding
LIMITES	
FOLGA MÁXIMA DO PNEU	700x33mm

Preço: 4 049,00 €

GEOMETRIA

QUADRO	XS	S	M	ML	L	XL
Comprimento do tubo do assento (mm)	425	445	470	500	530	560
Ângulo do tubo do assento	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Comprimento do tubo superior (mm)	520	535	550	565	580	600
Comprimento do tubo principal (mm)	120	130	145	165	185	200
Ângulo do tubo principal	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Garfo ancinho (mm)	45	45	45	45	45	45
Trilha (mm)	72,1	64	59,2	59,2	59,2	59,2
distância entre eixos (mm)	976	977	980	991	1006	1020
Comprimento Chain Stay (mm)	405	405	405	405	405	405
Suporte inferior (mm)	72	70	70	67	67	67
Pilha (mm)	517	528	545	562	581	596
Alcançar (mm)	376	383	388	393	402	412
Altura do standover (mm)	719	734	752	768	786	803
Largura do guidão (mm)	380	380	400	400	420	420
Comprimento da haste (mm)	80	90	100	110	110	120
Comprimento da Manivela (mm)	165	165	170	170	172,5	172,5

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.