TCR ADVANCED-UI2



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, M/L, L, XL
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	Giant Contact, 31.8mm, Reach 68mm & Drop 120mm (360-380mm), Reach 72mm & Drop 125mm (400-440mm) XS: 380mm, S: 380mm, M: 400mm, M/L: 400mm, L: 420mm, XL: 420mm
GRIPS	Stratus Lite 2.0 w/ gel
OPORA KRMILA	Giant Contact Aerolight, -10° XS: 80mm, S: 90mm, M: 100mm, M/L: 110mm, L: 110mm, XL: 120mm
OPORA SEDEŽA	Giant Variant, composite, -5/+15mm offset
SEDEŽ	Giant Approach, 7mm steel rail, with LiniClip / ParticleFlow technology
POGON	
PRESTAVNE ROČICE	Shimano Ultegra Di2 HRD
PREDNJI MENJALNIK	Shimano Ultegra Di2
ZADNJI MENJALNIK	Shimano Ultegra Di2
ZAVORE	Shimano Ultegra Di2 HRD hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
ZAVORNE ROČICE	Shimano Ultegra Di2 HRD
VERIŽNIK	Shimano CS-R8100, 11x34
VERIGA	Shimano CN-M8100, 12-speed
GONILKE Z VERIŽNIKI	Shimano Ultegra, 30/51 XS: 165mm, S: 165mm, M: 170mm, M/L: 170mm, L: 172.5mm, XL: 172.5mm
BOTTOM BRACKET	Shimano, press fit 71

OBROČNIKI	
OBROČI	Giant SLR 2 40 Carbon Disc WheelSystem
PESTA	Giant SLR 2 40 WheelSystem hubs (integrated)
PLAŠČI	Giant Gavia Course 0 tubeless, 700x30c, 170 TPI, folding
LIMITS	
MAX TIRE CLEARANCE	700x33mm

GEOMETRIJA

OKVIR	XS	S	M	ML	L	XL
Dolžina sedežne cevi (mm)	425	445	470	500	530	560
Kot sedežne cevi	74,5°	74,0°	73,5°	73,0°	73,0°	72,5°
Top Tube Length (mm)	520	535	550	565	580	600
Višina glave okvirja (mm)	120	130	145	165	185	200
Krmilni kot	71,0°	72,3°	73,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	45	45	45	45	45	45
Trail (mm)	72,1	64	59,2	59,2	59,2	59,2
Medosna razdalja (mm)	976	977	980	991	1006	1020
Dolžina cevi ob verigi (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	67	67	67
Oddaljenost zgornje cevi od gonilne osi (mm)	517	528	545	562	581	596
Doseg (mm)	376	383	388	393	402	412
Višina zgornje cevi (mm)	719	734	752	768	786	803
Širina krmila (mm)	380	380	400	400	420	420
Dolžina opore krmila (mm)	80	90	100	110	110	120
Dolžina gonilke (mm)	165	165	170	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.