

TCR ADVANCED-UI2



SPECS

RAM	
STORLEKAR	S, M, M/L, L, XL
RAM	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant Contact, 31.8mm, Reach 68mm & Drop 120mm (360-380mm), Reach 72mm & Drop 125mm (400-440mm) XS: 380mm, S: 380mm, M: 400mm, M/L: 400mm, L: 420mm, XL: 420mm
GREPPAR	Stratus Lite 2.0 w/ gel
STAM	Giant Contact Aerolight, -10° XS: 80mm, S: 90mm, M: 100mm, M/L: 110mm, L: 110mm, XL: 120mm
SADELSTOLPE	Giant Variant, composite, -5/+15mm offset
SADEL	Giant Approach, 7mm steel rail, with LiniClip / ParticleFlow technology
DRIVLINA	
VÄXLAR	Shimano Ultegra Di2 HRD
FRAMVÄXEL	Shimano Ultegra Di2
BAKVÄXEL	Shimano Ultegra Di2
BROMSAR	Shimano Ultegra Di2 HRD hydraulic, Shimano RT-CL700 rotors [F] 160mm, [R] 140mm
BROMSSPAKAR	Shimano Ultegra Di2 HRD
KASSETT	Shimano CS-R8100, 11x34
KEDJA	Shimano CN-M8100, 12-speed
VEVPARTI	Shimano Ultegra, 30/51 XS: 165mm, S: 165mm, M: 170mm, M/L: 170mm, L: 172.5mm, XL: 172.5mm
BROMSREGLAGE	Shimano, press fit 71

HJUL	
FÄLGAR	Giant SLR 2 40 Carbon Disc WheelSystem
NAV	Giant SLR 2 40 WheelSystem hubs (integrated)
DÄCK	Giant Gavia Course 0 tubeless, 700x30c, 170 TPI, folding
GRÄNSER	
MAX DÄCKAVSTÅND	700x33mm

Price: 48 000,00 kr

GEOMETRY

RAM	S	M	ML	L	XL
Längd sadelrör (mm)	445	470	500	530	560
Vinkel sadelrör	74,0°	73,5°	73,0°	73,0°	72,5°
Topprörets längd (mm)	535	550	565	580	600
Styrhuvud Längd (mm)	130	145	165	185	200
Vinkel styrhuvud	72,3°	73,0°	73,0°	73,0°	73,0°
Gaffelvinkel (mm)	45	45	45	45	45
Spår (mm)	64	59,2	59,2	59,2	59,2
Hjulbas (mm)	977	980	991	1006	1020
Kedjestagslängd (mm)	405	405	405	405	405
Nedre fäste Drop (mm)	70	70	67	67	67
Stack (mm)	528	545	562	581	596
Reach (mm)	383	388	393	402	412
Stå över höjden (mm)	734	752	768	786	803
Styrets bredd (mm)	380	400	400	420	420
Stamlängd (mm)	90	100	110	110	120
Vevlängd (mm)	165	170	170	172,5	172,5

All specifications listed are subject to change without notice.