

TOUGHROAD SLR 2

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Metal
FRAME	ALUXX SLR-Grade Aluminium, disc
FORK	Advanced-Grade Composite, alloy OverDrive steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XC, 31.8mm
GRIPS	Giant Connect Ergo
STEM	Giant Contact, 8-degree
SEATPOST	Giant D-Fuse
SADDLE	Giant Sport
PEDALS	Platform
DRIVETRAIN	
SHIFTERS	Shimano Altus, 2x9
FRONT DERAILLEUR	Shimano Acera
REAR DERAILLEUR	Shimano Alivio
BRAKES	Shimano BL-MT200 hydraulic, [F]160mm, [R]160mm rotors
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano CS-HG201, 11x36
CHAIN	KMC X9 with Missing Link
CRANKSET	ProWheel forged alloy, 28/44 with chainguard S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Cartridge

WHEELS	
RIMS	Giant double wall aluminium
HUBS	Alloy, 28h
SPOKES	Stainless, 14g
TIRES	Giant Sycamore S, 700x50c, FlatGuard Deflect 2
EXTRAS	X-DeFender protection, 53mm max tyre size

Price: \$1,999.00

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	420	460	510	550
Seat Tube Angle	73.0°	73.0°	72.0°	71.5°
Top Tube Length (mm)	585	595	605	620
Head Tube Length (mm)	125	150	170	190
Head Tube Angle	71.5°	71.5°	72.0°	72.0°
Fork Rake (mm)	42	42	42	42
Trail (mm)	78.3	78.3	74.9	74.9
Wheelbase (mm)	1067	1078	1071	1080
Chain Stay Length (mm)	450	450	450	450
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	578	602	623	642
Reach (mm)	408	411	403	405
Stand Over Height (mm)	724	754	795	864
Stem Length (mm)	90	100	110	110
Crank Length (mm)	170	175	175	175
Wheel Size	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.