

# TOUGHROAD SLR 2

**GIANT**



## SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Metal
FRAME	ALUXX SLR-Grade Aluminum, disc
FORK	Advanced-Grade Composite, alloy OverDrive steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XC, 31.8mm S:64cm, M:68cm, L:68cm, XL:68cm
GRIPS	Giant Connect Ergo
STEM	Giant Contact, 8-degree S:60mm, M:70mm, L:80mm, XL:90mm
SEATPOST	Giant D-Fuse, alloy, 350mm
SADDLE	Giant Sport
PEDALS	platform
DRIVETRAIN	
SHIFTERS	Shimano Altus, 2x9
FRONT DERAILLEUR	Shimano Acera
REAR DERAILLEUR	Shimano Alivio
BRAKES	Shimano BL-MT200 hydraulic, [F]160mm, [R]160mm rotors
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano CS-HG201, 11x36
CHAIN	KMC X9 with Missing Link
CRANKSET	ProWheel forged alloy, 28/44 with chainguard S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant double wall aluminum
HUBS	alloy, 28h
SPOKES	stainless, 14g
TIRES	Giant Sycamore S, 700x50c, FlatGuard Deflect 2
EXTRAS	X-DeFender protection, 53mm max tire size

## GEOMETRY

FRAME	XS	S	M	L	XL
Seat Tube Length (mm)	390	420	460	510	550
Seat Tube Angle	73,0°	73,0°	73,0°	72,0°	71,5°
Top Tube Length (mm)	580	585	595	605	620
Head Tube Length (mm)	100	125	150	170	190
Head Tube Angle	71,5°	71,5°	71,5°	72,0°	72,0°
Fork Rake (mm)	42	42	42	42	42
Trail (mm)	78,3	78,3	78,3	74,9	74,9
Wheelbase (mm)	1061	1067	1078	1071	1080
Chain Stay Length (mm)	450	450	450	450	450
Bottom Bracket Drop (mm)	70	70	70	70	70
Stack (mm)	555	578	602	623	642
Reach (mm)	410	408	411	403	405
Stand Over Height (mm)	696	724	754	795	864
Handlebar Width (mm)	640	640	690	690	690
Stem Length (mm)	80	90	100	110	110
Crank Length (mm)	165	170	170	175	175
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.