



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Metal
OKVIR	ALUXX SLR-Grade Aluminum, disc
VILICE	Advanced-Grade Composite, alloy OverDrive steerer, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Connect XC, 31.8mm S:64cm, M:68cm, L:68cm, XL:68cm
GRIPS	Giant Connect Ergo
OPORA KRMILA	Giant Contact, 8-degree S:60mm, M:70mm, L:80mm, XL:90mm
OPORA SEDEŽA	Giant D-Fuse, alloy, 350mm
SEDEŽ	Giant Sport
PEDALA	platform
POGON	
PRESTAVNE ROČICE	Shimano Altus, 2x9
PREDNJI MENJALNIK	Shimano Acera
ZADNJI MENJALNIK	Shimano Alivio
ZAVORE	Shimano BL-MT200 hydraulic, [F]160mm, [R]160mm rotors
ZAVORNE ROČICE	Shimano BL-MT200
VERIŽNIK	Shimano CS-HG201, 11x36
VERIGA	KMC X9 with Missing Link
GONILKE Z VERIŽNIKI	ProWheel forged alloy, 28/44 with chainguard S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	cartridge

OBROČNIKI

OBROČI	Giant double wall aluminum
PESTA	alloy, 28h
NAPERE	stainless, 14g
PLAŠČI	Giant Sycamore S, 700x50c, FlatGuard Deflect 2
DODATKI	X-DeFender protection, 53mm max tire size

GEOMETRIJA

OKVIR	XS	S	M	L	XL
Dolžina sedežne cevi (mm)	390	420	460	510	550
Kot sedežne cevi	73,0°	73,0°	73,0°	72,0°	71,5°
Top Tube Length (mm)	580	585	595	605	620
Višina glave okvirja (mm)	100	125	150	170	190
Krmilni kot	71,5°	71,5°	71,5°	72,0°	72,0°
Zamik vpetja osi (mm)	42	42	42	42	42
Trail (mm)	78,3	78,3	78,3	74,9	74,9
Medosna razdalja (mm)	1061	1067	1078	1071	1080
Dolžina cevi ob verigi (mm)	450	450	450	450	450
Bottom Bracket Drop (mm)	70	70	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	555	578	602	623	642
Doseg (mm)	410	408	411	403	405
Višina zgornje cevi (mm)	696	724	754	795	864
Širina krmila (mm)	640	640	690	690	690
Dolžina opore krmila (mm)	80	90	100	110	110
Dolžina gonilke (mm)	165	170	170	175	175
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.