



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Metallic Black / Black, Slate Gray / Black
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICE	Marzocchi Z2, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float DPS Performance, 185/50, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact TR35, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SEDEŽ	Giant Romero
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Deore, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore
ZAVORE	Shimano Deore BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano BL-MT401
VERIŽNIK	Shimano Deore, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Praxis Cadet M24, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Praxis, press fit

## OBROČNIKI

OBROČI	Giant AM 29 tubeless ready sleeve-joint rim, 30mm inner width
PESTA	alloy, sealed
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size

## GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	420		430		465		496	
Kot sedežne cevi	77,2°	78,0°	76,3°	77,0°	76,3°	77,0°	76,3°	77,0°
Top Tube Length (mm)	561	559	599	597	626	624	663	661
Višina glave okvirja (mm)	100		110		120		130	
Krmilni kot	65,4°	66,2°	65,5°	66,2°	65,5°	66,2°	65,5°	66,2°
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	126	120	126	120	126	120	126	120
Medosna razdalja (mm)	1166	1165	1195	1194	1224	1223	1263	1262
Dolžina cevi ob verigi (mm)	439	437	439	437	439	437	439	437
Bottom Bracket Drop (mm)	45	35	45	35	45	35	45	35
Oddaljenost zgornje cevi od gonilne osi (mm)	610	604	619	613	628	622	637	631
Doseg (mm)	422	431	447	456	472	480	507	515
Višina zgornje cevi (mm)	730	738	725	734	749	759	771	780
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	40		40		50		50	
Dolžina gonilke (mm)	165		170		170		170	
Velikost obročnikov	29"		29"		29"		29"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.