



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Blue Dragonfly/Black/Chrome
FRAME	Advanced-grade composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
FORK	Fox 34 Performance Elite, 130mm, GRIP 2, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X Performance Elite, 185/50, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, composite, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission
BRAKES	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAIN	SRAM GX Eagle Transmission
CRANKSET	SRAM GX Eagle Transmission, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM, press fit

WHEELS	
RIMS	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
HUBS	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPOKES	Sapim
TIRES	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	420	430	465	496
Seat Post Insertion Depth (mm)	290	300	335	366
Seat Tube Angle	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°
Top Tube Length (mm)	561 559	599 597	626 624	663 661
Head Tube Length (mm)	100	110	120	130
Head Tube Angle	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°
Fork Rake (mm)	44	44	44	44
Trail (mm)	126 120	126 120	126 120	126 120
Wheelbase (mm)	1166 1165	1195 1194	1124 1123	1263 1262
Chain Stay Length (mm)	439 437	439 437	439 437	439 437
Bottom Bracket Drop (mm)	45 35	45 35	45 35	45 35
Stack (mm)	610 604	619 613	628 622	637 631
Reach (mm)	422 431	447 456	472 480	507 515
Stand Over Height (mm)	729 737	723 732	746 755	751 760
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.