

TRANCE ADVANCED 29 1

GIANT



TEKNISET TIEDOT

| RUNKO | |
|----------------|---|
| KOOT | S, M, L, XL |
| VÄRIT | Blue Dragonfly/Black/Chrome |
| RUNKO | Advanced-grade composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage |
| HAARUKKA | Fox 34 Performance Elite, 130mm, GRIP 2, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant |
| ISKUNVAIMENNIN | Fox Float X Performance Elite, 185/50, custom tuned for Giant |
| KOMPONENTIT | |
| OHJAUSTANKO | Giant Contact SLR TR35, composite, 780x35mm |
| GRIPIT | Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm |
| OHJAINKANNATIN | Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm |
| SATULATOLPPA | TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm |
| SATULA | Giant Romero SL |
| POLKIMET | N/A |
| VOIMANSIIRTO | |
| VAIHDEVIPU | SRAM AXS Pod, discrete clamp, 1x12 |
| ETUVAIHTAJA | N/A |
| TAKAVAIHTAJA | SRAM GX Eagle Transmission |
| JARRUT | Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm |
| JARRUKAHVAT | Shimano Deore XT BL-M8100 |
| RATASPAKKA | SRAM GX Eagle Transmission, 10x52 |
| KETJUT | SRAM GX Eagle Transmission |
| KAMPISARJA | SRAM GX Eagle Transmission, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm |
| KESKIÖ | SRAM, press fit |

| RENKAAT | |
|------------|---|
| VANTEET | Giant TRX 2 29 Carbon WheelSystem, 30mm inner width |
| NAVAT | Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt |
| PINNAT | Sapim |
| RENKAAT | [F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless |
| LISÄTIEDOT | tubeless prepared, 2.6" max tire size, 34t max chainring size |

Suositusuhinta: 7 989,00 €

GEOMETRIA

| RUNKO | S | M |
|------------------------------------|---------------|---------------|
| | LOW HIGH | LOW HIGH |
| Satulaputken pituus (mm) | 420 | 430 |
| Satulatolpan asennussyvyys (mm) | 290 | 300 |
| Satulaputken kulma | 77,2° 78,0° | 76,3° 77,0° |
| Vaakaputken pituus (mm) | 561 559 | 599 597 |
| Emäputken pituus (mm) | 100 | 110 |
| Emäputken kulma | 65,4° 66,2° | 65,5° 66,2° |
| Haarukan offset (mm) | 44 | 44 |
| Trail-mitta (mm) | 126 120 | 126 120 |
| Akseliväli (mm) | 1166 1165 | 1195 1194 |
| Takahaarukan alaputken pituus (mm) | 439 437 | 439 437 |
| Keskion pudotus (mm) | 45 35 | 45 35 |
| Stack-mitta (mm) | 610 604 | 619 613 |
| Reach-mitta (mm) | 422 431 | 447 456 |
| Standover-mitta (mm) | 729 737 | 723 732 |
| Ohjaustangon leveys (mm) | 780 | 780 |
| Ohjainkannattimen pituus (mm) | 40 | 40 |
| Kammen pituus (mm) | 165 | 170 |
| Rengaskoko | 29" | 29" |

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.