

TRANCE ADVANCED 29 1



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Blue Dragonfly/Black/Chrome
CADRE	Advanced-grade composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
FOURCHE	Fox 34 Performance Elite, 130mm, GRIP 2, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTISSEUR	Fox Float X Performance Elite, 185/50, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact SLR TR35, composite, 780x35mm
POIGNÉES	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	NEW Contact Switch AT DSP with remote lever, 30,9mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	SRAM AXS Pod, discrete clamp, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle T-Type AXS
FREINS	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
LEVIER DE FREIN	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX Eagle Transmission, 10x52
CHAÎNE	SRAM GX Eagle Transmission
PÉDALIER	SRAM GX Eagle Transmission, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	SRAM, press fit

ROUES	
JANTES	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
MOYEURS	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
RAYONS	Sapim
PNEUS	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 7 500,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	420		430		465		496	
Seat Post Insertion Depth (mm)	290		300		335		366	
Angle de tube de selle	77,2°	78,0°	76,3°	77,0°	76,3°	77,0°	76,3°	77,0°
Longueur du tube supérieur (mm)	561	559	599	597	626	624	663	661
Longueur du tube de direction (mm)	100		110		120		130	
Angle du tube de direction	65,4°	66,2°	65,5°	66,2°	65,5°	66,2°	65,5°	66,2°
Déport de fourche (mm)	44		44		44		44	
Trail (mm)	126	120	126	120	126	120	126	120
Empattement (mm)	1166	1165	1195	1194	1124	1123	1263	1262
Longueur des bases (mm)	439	437	439	437	439	437	439	437
Drop du boîtier de pédalier (mm)	45	35	45	35	45	35	45	35
Stack (mm)	610	604	619	613	628	622	637	631
Reach (mm)	422	431	447	456	472	480	507	515
Hauteur en statique (mm)	729	737	723	732	746	755	751	760
Largeur de cintre (mm)	780		780		780		780	
Longueur de potence (mm)	40		40		50		50	
Longueur des manivelles (mm)	165		170		170		170	
Diamètre des roues	29"		29"		29"		29"	

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.