

# TRANCE ADVANCED 29 1

**GIANT**



## SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Blue Dragonfly/Black/Chrome
FRAME	Advanced-grade composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
VOORVORK	Fox 34 Performance Elite, 130mm, GRIP 2, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DEMPER	Fox Float X Performance Elite, 185/50, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact SLR TR35, composite, 780x35mm
HANDVATTEN	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ZADELPEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
ZADEL	Giant Romero SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM GX Eagle Transmission
REMMEN	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
REMHENDELS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX Eagle Transmission, 10x52
AANDRIJVING	SRAM GX Eagle Transmission
CRANKSET	SRAM GX Eagle Transmission, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM, press fit

WIELSET	
VELGEN	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAVEN	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPAKEN	Sapim
BANDEN	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRA'S	tubeless prepared, 2.6" max tire size, 34t max chainring size

Adviesprijs: € 7.699,00

## GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	420	430	430	465	465	496		
Seat Post Insertion Depth (mm)	290	300	335	366				
Zitbuis Hoek	77,2°   78,0°	76,3°   77,0°	76,3°   77,0°	76,3°   77,0°	76,3°   77,0°	76,3°   77,0°		
Frame Lengte (horizontaal) (mm)	561   559	599   597	626   624	663   661				
Balhoofdbuis Lengte (mm)	100	110	120	130				
Balhoofdbuis Hoek	65,4°   66,2°	65,5°   66,2°	65,5°   66,2°	65,5°   66,2°	65,5°   66,2°			
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	126   120	126   120	126   120	126   120	126   120			
Wielbasis (mm)	1166   1165	1195   1194	1124   1123	1263   1262				
Liggende achtervork lengte (mm)	439   437	439   437	439   437	439   437				
Bottom Bracket Drop (mm)	45   35	45   35	45   35	45   35				
Stack (mm)	610   604	619   613	628   622	637   631				
Reach (mm)	422   431	447   456	472   480	507   515				
Stand Over Height (mm)	729   737	723   732	746   755	751   760				
Stuur breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	40	40	50	50				
Cranklengte (mm)	165	170	170	170				
Wielmaat	29"	29"	29"	29"				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.