

# TRANCE ADVANCED 29 1

**GIANT**

## SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Blue Dragonfly/Black/Chrome
OKVIR	Advanced-grade composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
VILICE	Fox 34 Performance Elite, 130mm, GRIP 2, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float X Performance Elite, 185/50, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, discrete clamp, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle Transmission
ZAVORE	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore XT BL-M8100
VERIŽNIK	SRAM GX Eagle Transmission, 10x52
VERIGA	SRAM GX Eagle Transmission
GONILKE Z VERIŽNIKI	SRAM GX Eagle Transmission, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM, press fit

OBROČNIKI	
OBROČI	Giant TRX 2.29 Carbon WheelSystem, 30mm inner width
PESTA	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size

## GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	420	430	465	496				
Seat Post Insertion Depth (mm)	290	300	335	366				
Kot sedežne cevi	77,2°   78,0°	76,3°   77,0°	76,3°   77,0°	76,3°   77,0°				
Top Tube Length (mm)	561   559	599   597	626   624	663   661				
Višina glave okvirja (mm)	100	110	120	130				
Krmični kot	65,4°   66,2°	65,5°   66,2°	65,5°   66,2°	65,5°   66,2°				
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	126   120	126   120	126   120	126   120				
Medosna razdalja (mm)	1166   1165	1195   1194	1124   1123	1263   1262				
Dolžina cevi ob verigi (mm)	439   437	439   437	439   437	439   437				
Bottom Bracket Drop (mm)	45   35	45   35	45   35	45   35				
Oddaljenost zgornje cevi od gonilne osi (mm)	610   604	619   613	628   622	637   631				
Doseg (mm)	422   431	447   456	472   480	507   515				
Višina zgornje cevi (mm)	729   737	723   732	746   755	751   760				
Širina krmila (mm)	780	780	780	780				
Dolžina opore krmila (mm)	40	40	50	50				
Dolžina gonilke (mm)	165	170	170	170				
Velikost obročnikov	29"	29"	29"	29"				

Vse navedene specifikacije se lahko spremenijo brez obvestila.