

TRANCE ADVANCED 29 2

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Carbon/Supernova/Chrome
FRAME	Advanced-grade composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
VOORVORK	Fox 34 Float Rhythm, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DEMPER	Fox Float Performance, 185/50, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact TR35, 780x35mm
HANDVATTEN	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ZADELPEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
ZADEL	Giant Romero SL
PEDALEN	platform [GC,GT]
AFMONTAGE	
SHIFTERS	Shimano SLX SL-M7100, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano SLX RD-M7100
REMMEN	Shimano Deore BR-M6120, hydraulic, Shimano RT-56 rotors [F]180mm, [R]180mm
REMHENDELS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX, 10x51
AANDRIJVING	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAVEN	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPAKEN	Sapim
BANDEN	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRA'S	tubeless prepared, 2.6" max tire size, 34t max chainring size

Adviesprijs: € 5.499,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	420	430	465	496				
Seat Post Insertion Depth (mm)	290	300	335	366				
Zitbuis Hoek	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°		
Frame Lengte (horizontaal) (mm)	561 559	599 597	626 624	663 661				
Balhoofdbuis Lengte (mm)	100	110	120	130				
Balhoofdbuis Hoek	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°		
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	126 120	126 120	126 120	126 120	126 120	126 120		
Wielbasis (mm)	1166 1165	1195 1194	1124 1123	1263 1262				
Liggende achtervork lengte (mm)	439 437	439 437	439 437	439 437	439 437	439 437		
Bottom Bracket Drop (mm)	45 35	45 35	45 35	45 35	45 35	45 35		
Stack (mm)	610 604	619 613	628 622	637 631				
Reach (mm)	422 431	447 456	472 480	507 515				
Stand Over Height (mm)	729 737	723 732	746 755	751 760				
Stuur breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	40	40	50	50				
Cranklengte (mm)	165	170	170	170				
Wielmaat	29"	29"	29"	29"				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.