

TRANCE ADVANCED E+ 0



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
CONTROLLER	Giant RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO LUX, frame integrated LED display ANT+
BATTERY	EnergyPak Smart 840Wh EnergyPak Plus 280 range extender compatible
CHARGER	48V 4A Smart Charger X
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
FRAME	
SIZES	S, M, L, XL
COLOURS	Prismatic Haze
FRAME	Advanced-grade composite, Advanced Forged Composite Upper Rocker, 150mm Maestro suspension system, 3 position flip chip, UDH hanger 12x148mm thru-axle
FORK	Fox 36 Factory, 160mm travel, 44mm offset, GRIP X damper, Kabolt-X 15x110mm thru-axle
SHOCK	Fox Float X Factory, EVOL Large Volume sleeve, 2 position lever, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail, integrated carbon 1-piece handlebar, 20mm Rise, 40/45/50mm Reach Adjust, +3/0/-3degree Angle Adjust System
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SLR Trail, integrated carbon 1-piece handlebar, 20mm Rise, 40/45/50mm Reach Adjust, +3/0/-3degree Angle Adjust System
SEATPOST	Giant Contact Switch E, electronic travel-adjust dropper post S: 140mm travel / 30.9 x 457mm M:170mm travel / 30.9 x 514mm L: 170mm travel / 30.9 x 514mm XL: 200mm travel / 30.9 x 574mm
SADDLE	Giant Romero SL HD
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, Rocker Paddle, 1x12
REAR DERAILLEUR	SRAM X0 Eagle Transmission AXS
BRAKES	TRP EVO Pro, hydraulic, TRP 2.3mm rotors [F]220mm, [R]203mm
BRAKE LEVERS	TRP EVO Pro
CASSETTE	SRAM GX XS-1275 Eagle Transmission 10-52T
CHAIN	KMC eFlatHT
CRANKSET	Praxis Performance Carbon e-crank arms SRAM Eagle Transmission steel direct mount, 36T chain ring S:155mm, M: 155mm, L:155mm, XL:155mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant TRX Hookless Tubeless ready Carbon 29" [F] 27.5" [R] 30mm inner width
HUBS	[F] Giant E-TRX MTB Alloy Hub, 6 Bolt, 28H [R] Giant E-TRX MTB Alloy Hub, SRAM XD Drive Body 72T Helical-Bevel Ratchet Driver, 6 Bolt, 28H
SPOKES	Sapim Laser, e-bike optimised
TYRES	Maxxis Assagai 29x2.5" foldable, Tubeless, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" foldable, Tubeless, EXO+ 3C Maxx Terra [R]
EXTRAS	Tyre Pressure Management System, Torx 25 Battery Lock with built-in Torque limiter, Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
FENDER/CHAINGUARD	Co-moulded guide 32-36T adjustable

Price: \$14,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Seat Tube Angle	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°
Top Tube Length (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Head Tube Length (mm)	110			120			130			140		
Head Tube Angle	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	135.9			135.9			135.9			135.9		
Wheelbase (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1297
Chain Stay Length (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Bottom Bracket Drop (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	658
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	155			155			155			155		
Wheel Size	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.