

TRANCE ADVANCED E+ 0



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
COMMANDE	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
ECRAN	RideControl GO Lux
BATTERIE	EnergyPak 840Wh, 48V
ENERGYPAK PLUS COMPATIBLES	EnergyPakPlus 280Wh
CHARGEUR	48V 4A Smart Charger X
CONNECTIVITÉ	E-Lock, FindMyBike, Tire Checker Aegis
CADRE	
TAILLES	S, M, L, XL
COLORIS	Prismatic Haze
CADRE	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FOURCHE	Fox 36 Factory, 160mm travel, GripX damper
AMORTISSEUR	Fox Float X, Factory 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact SLR Trail Integrated, Carbon, 20mm rise, 7°/8°/9° effective sweep adjustable
POIGNÉES	Giant Tactal Pro
POTENCE	Giant Contact SLR Trail Integrated, Carbon, 40/45/50mm Reach adjustable
TIGE DE SELLE	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SELLE	Giant Romero SL HD
DÉRAILLEUR	
MANETTES	Sram AXS Pod Rocker, discrete clamp
DÉRAILLEUR ARRIÈRE	SRAM XO AXS
FREINS	TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
LEVIER DE FREIN	TRP EVO Pro
CASSETTE	SRAM Eagle Transmission, XS-1275, 10-52T, 12-speed
CHAÎNE	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
PÉDALIER	Praxis TYPE-2 carbon , SRAM XX Eagle Transmission 36T

ROUES	
JANTES	Giant TRX HD, Carbon, 30mm inner width, WideGuard Technology
MOYEUX	Giant TRX HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RAYONS	Giant TRX HD, Dynamic Balanced Lacing (D.B.L.)
PNEUS	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure monitoring system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
GARDE-BOUE / CHAÎNE	Co-molded guide 32-36T adjustable

Prix Public Conseillé: 10 000,00 €

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Angle de tube de selle	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°
Longueur du tube supérieur (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Longueur du tube de direction (mm)	110			120			130			140		
Angle du tube de direction	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°
Déport de fourche (mm)	44			44			44			44		
Trail (mm)	135,9			135,9			135,9			135,9		
Empattement (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1297
Longueur des bases (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Drop du boîtier de pédalier (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	657
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	515
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			40			40		
Longueur des manivelles (mm)	155			155			155			155		
Diamètre des roues	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.