

TRANCE ADVANCED E+ 0



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
COMANDO	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO Lux
BATTERIA	EnergyPak 840Wh, 48V
CARICATORE	48V 4A Smart Charger X
TELAIO	
TAGLIE	S/M/L/XL
TELAIO	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORCELLA	Fox 36 Factory, 160mm travel, GripX damper
AMMORTIZZATORE	Fox Float X, Factory 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
COMPONENTISTICA	
MANUBRIO	Giant Contact SLR Trail Integrated, Carbon, 20mm rise, 7°/8°/9° effective sweep adjustable
MANOPOLE	Giant Tactal Pro
ATTACCO MANUBRIO	Giant Contact SLR Trail Integrated, Carbon, 40/45/50mm Reach adjustable
REGGISSELLA	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SELLA	Giant Romero SL HD
SISTEMA DI TRASMISSIONE	
CAMBIO	Sram AXS Pod Rocker, discrete clamp
DERAGLIATORE POSTERIORE	SRAM XO AXS
FRENI	TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
COMANDI FRENO	TRP EVO Pro
PACCO PIGNONI	SRAM Eagle Transmission, XS-1275, 10-52T, 12-speed
CATENA	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
GUARNITURA	Praxis TYPE-2 carbon , SRAM XX Eagle Transmission 36T

RUOTE	
CERCHI	Giant TRX HD, Carbon, 30mm inner width, WideGuard Technology
MOZZI	Giant TRX HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RAGGI	Giant TRX HD, Dynamic Balanced Lacing (D.B.L.)
COPERTONI	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRA	Giant Aegis Tire Checker, included tire pressure monitoring system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
PARAFANGO / PARACATENA	Co-molded guide 32-36T adjustable

Prezzo: 9.999,00 €

GEOMETRIA

TELAIO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Lunghezza Tubo Sella (mm)	400			425			450			475
Profondità inserimento reggisella (mm)	245			270			295			310
Angolo Tubo Sella	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°
Lunghezza Tubo Orizzontale (mm)	568	567	566	605	604	603	630	629	628	662
Lunghezza Tubo Sterzo (mm)	110			120			130			140
Angolo Sterzo	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°
Rake Forcella (mm)	44			44			44			44
Avancorsa (mm)	135,9			135,9			135,9			135,9
Interasse (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300
Lunghezza Carro Posteriore (mm)	443	443	443	443	443	443	443	443	443	443
Drop Movimento Centrale (mm)	17	12	7	17	12	7	17	12	7	17
Stack (mm)	634	631	629	643	640	638	652	649	647	661
Reach (mm)	422	425	428	457	460	463	477	480	484	504
Larghezza Manubrio c/c (mm)	800			800			800			800
Lunghezza Attacco Manubrio (mm)	40			40			40			40
Lunghezza Pedivella (mm)	155			155			155			155
Dimensione Ruote	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 2

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.