

TRANCE ADVANCED E+ 0



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
SENSOR	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
ECRÃ	RideControl GO Lux
BATERIA	EnergyPak 840Wh, 48V
CARREGADOR	48V 4A Smart Charger X
QUADRO	
TAMANHOS	S/M/L/XL
QUADRO	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORQUILHA	Fox 36 Factory, 160mm travel, GripX damper
AMORTECEDORES	Fox Float X, Factory 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
COMPONENTES	
GUIADOR	Giant Contact SLR Trail Integrated, Carbon, 20mm rise, 7°/8°/9° effective sweep adjustable
PUNHOS	Giant Tactal Pro
AVANÇO	Giant Contact SLR Trail Integrated, Carbon, 40/45/50mm Reach adjustable
ESPIGÃO DE SELIM	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SELIM	Giant Romero SL HD
TRANSMISSÃO	
MANETES	Sram AXS Pod Rocker, discrete clamp
DESVIADOR TRASEIRO	SRAM XO AXS
TRAVÕES	TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
MANÍPULOS DOS TRAVÕES	TRP EVO Pro
CASSETTE	SRAM Eagle Transmission, XS-1275, 10-52T, 12-speed
CORRENTE	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
CONJUNTO PEDALEIRO	Praxis TYPE-2 carbon , SRAM XX Eagle Transmission 36T

RODAS	
AROS	Giant TRX HD, Carbon, 30mm inner width, WideGuard Technology
CUBOS	Giant TRX HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RAIOS	Giant TRX HD, Dynamic Balanced Lacing (D.B.L.)
PNEUS	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure monitoring system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACESSÓRIOS	
GUARDA LAMAS/PROTECTOR DE CORRENTE	Co-molded guide 32-36T adjustable

Preço: 8 799,00 €

GEOMETRIA

QUADRO	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Comprimento do tubo do assento (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Ângulo do tubo do assento	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°
Comprimento do tubo superior (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Comprimento do tubo principal (mm)	110			120			130			140		
Ângulo do tubo principal	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°
Garfo ancinho (mm)	44			44			44			44		
Trilha (mm)	135,9			135,9			135,9			135,9		
distância entre eixos (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1297
Comprimento Chain Stay (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Suporte inferior (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Pilha (mm)	634	631	629	643	640	638	652	649	647	661	658	656
Alcançar (mm)	422	425	428	457	460	463	477	480	484	504	507	510
Largura do guidão (mm)	800			800			800			800		
Comprimento da haste (mm)	40			40			40			40		
Comprimento da Manivela (mm)	155			155			155			155		
Tamanho da roda	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.