

TRANCE ADVANCED E+ 0



SPECS

HYBRID CYKELTEKNIK	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
KONTROLLER	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
VISA	RideControl GO Lux
BATTERI	EnergyPak 840Wh, 48V
LADDARE	48V 4A Smart Charger X
RAM	
STORLEKAR	S/M/L/XL
RAM	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
GAFFEL	Fox 36 Factory, 160mm travel, GripX damper
BAKDÄMPARE	Fox Float X, Factory 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
KOMPONENTER	
STYRE	Giant Contact SLR Trail Integrated, Carbon, 20mm rise, 7°/8°/9° effective sweep adjustable
GREPPAR	Giant Tactal Pro
STAM	Giant Contact SLR Trail Integrated, Carbon, 40/45/50mm Reach adjustable
SADELSTOLPE	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SADEL	Giant Romero SL HD
DRIVLINAN	
VÄXLAR	Sram AXS Pod Rocker, discrete clamp
BAKVÄXEL	SRAM XO AXS
BROMSAR	TRP EVO Pro, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BROMSSPAKAR	TRP EVO Pro
KASSETT	SRAM Eagle Transmission, XS-1275, 10-52T, 12-speed
KEDJA	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
VEVPARTI	Praxis TYPE-2 carbon , SRAM XX Eagle Transmission 36T

HJUL	
FÄLGAR	Giant TRX HD, Carbon, 30mm inner width, WideGuard Technology
NAV	Giant TRX HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
EKRAR	Giant TRX HD, Dynamic Balanced Lacing (D.B.L.)
DÄCK	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAFUNKTIONER	Giant Aegis Tire Checker, included tire pressure monitoring system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
TILLBEHÖR	
STÄNKSKÄRM/KEDJESKYDD	Co-molded guide 32-36T adjustable

Price: 118 000,00 kr

GEOMETRY

RAM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Längd sadelrör (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Vinkel sadelrör	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°
Topprörets längd (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Styrhuvud Längd (mm)	110			120			130			140		
Vinkel styrhuvud	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°
Gaffelvinkel (mm)	44			44			44			44		
Spår (mm)	135,9			135,9			135,9			135,9		
Hjulbas (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1297
Kedjestagslängd (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Nedre fäste Drop (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	658
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Styrets bredd (mm)	800			800			800			800		
Stamlängd (mm)	40			40			40			40		
Vevlängd (mm)	155			155			155			155		
Hjulstorlek	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

All specifications listed are subject to change without notice.