

TRANCE ADVANCED E+ 1



SPECIFIKACE

HYBRIDNÍ TECHNOLOGIE	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
OVLÁDACÍ JEDNOTKA	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLEJ	RideControl GO Lux
BATERIE	EnergyPak 840Wh, 48V
NABÍJEČKA	48V 4A Smart Charger X
RÁM	
VELIKOSTI	S/M/L/XL
BARVA	Carbon/Tactical Grey, Dusted Peri
RÁM	Advanced Composite frame, Advanced Forged Composite upper rocker, 150mm Maestro Suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 headset compatible
VIDLICE	Fox 36 Performance, 160mm travel, Grip damper
TLUMIČ	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
KOMPONENTY	
ŘÍDÍTKA	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPY	Giant Tactal Pro
PŘEDSTAVEC	Giant Contact SL Trail integrated, 40mm
SEDLOVKA	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SEDLO	Giant Romero SL HD
OSAZENÍ	
ŘAZENÍ	Sram AXS Pod Rocker, discrete clamp
PŘEHAZOVAČKA	SRAM GX AXS
BRZDY	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BRZDOVÉ PÁKY	TRP EVO Expert
KAZETA	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
ŘETĚZ	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
KLIKY	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

KOLA	
RÁFKY	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
NÁBOJE	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
DRÁTY	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
PLÁŠTĚ	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
DOPLŇKY	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
PŘÍSLUŠENSTVÍ	
OSTATNÍ	Co-molded guide 32-36T adjustable

Cena: 199 999 Kč

GEOMETRIE

RÁM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Délka sedlové trubky (mm)	400			425			450			475		
Max. zasunutí sedlovky (mm)	245			270			295			310		
Úhel sedlové trubky	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°
Délka horní trubky (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Délka hlavové trubky (mm)	110			120			130			140		
Úhel hlavové trubky	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°
Offset vidlice (mm)	44			44			44			44		
Trail (mm)	135,9			135,9			135,9			135,9		
Rozvor (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1298
Délka řetězové vzpěry (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Bottom Bracket Drop (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	658
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Šířka řídicítek (mm)	800			800			800			800		
Délka představce (mm)	40			40			40			40		
Délka klik (mm)	155			155			155			155		
Rozměr kol	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.