

TRANCE ADVANCED E+ 1



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
KONTROLLER	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO Lux
BATTERI	EnergyPak 840Wh, 48V
LADER	48V 4A Smart Charger X
RAMME	
STØRRELSER	S/M/L/XL
RAMME	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORGAFFEL	Fox 36 Performance, 160mm travel, Grip damper
BAGDÆMPER	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
KOMPONENTER	
STYR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GREB / STYRBÅND	Giant Tactal Pro
FREMPIND	Giant Contact SL Trail integrated, 40mm
SADELPIND	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SADEL	Giant Romero SL HD
GEARGRUPPE	
SKIFTEGREB	Sram AXS Pod Rocker, discrete clamp
BAGSKIFTER	SRAM GX AXS
BREMSE	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BREMSEGREB	TRP EVO Expert
KASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
KÆDE	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
KRANKSÆT	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

HJUL	
FÆLGE	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
NAV	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
EGER	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
DÆK	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EKSTRA	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
TILBEHØR	
SKÆRM / KÆDESKÆRM	Co-molded guide 32-36T adjustable

Pris: 63.529,00 kr.

GEOMETRI

RAMME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sadelrørlængde (mm)	400			425			450			475		
Sadelpindindsætningsdybde (mm)	245			270			295			310		
Sadelrørsvinkel	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°
Overrørlængde (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Kronrørlængde (mm)	110			120			130			140		
Kronrørsvinkel	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°
Forgaffel fremspring (rake) (mm)	44			44			44			44		
Sti (mm)	135,9			135,9			135,9			135,9		
Akselafstand (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1297
Kædestagslængde (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Krankboks drop (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	656
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	515
Styrbredde (mm)	800			800			800			800		
Frempindslængde (mm)	40			40			40			40		
Pedalarmslængde (mm)	155			155			155			155		
Hjulstørrelse	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Alle de anførte specifikationer kan ændres uden varsel.