

TRANCE ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
CONTROLLER	Giant RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO LUX, frame integrated LED display ANT+
BATTERY	EnergyPak Smart 840Wh EnergyPak Plus 280 range extender compatible
CHARGER	48V 4A Smart Charger X
MAXIMUM ASSISTED SPEED	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
FRAME	
SIZES	S, M, L, XL
COLOURS	Carbon/Tactical Grey, Dusted Peri
FRAME	Advanced-grade composite, Advanced Forged Composite Upper Rocker, 150mm Maestro suspension system, 3 position flip chip, UDH hanger 12x148mm thru-axle
FORK	Fox 36 Performance, 160mm travel, 44mm offset, GRIP damper, 3 position, Kabolt-X 15x110mm thru-axle
SHOCK	Fox Float X Performance, EVOL Large Volume sleeve, 2 position lever, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact SL Trail integrated, alloy, 27mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL Trail integrated, alloy, 27mm rise S:50mm, M:50mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch E, electronic travel-adjust dropper post S: 140mm travel / 30.9 x 457mm M:170mm travel / 30.9 x 514mm L: 170mm travel / 30.9 x 514mm XL: 200mm travel / 30.9 x 574mm
SADDLE	Giant Romero HD
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, Rocker Paddle, 1x12
REAR DERAILLEUR	SRAM GX Eagle Transmission AXS
BRAKES	TRP EVO Expert, hydraulic, TRP 2.3mm rotors [F]220mm, [R]203mm
BRAKE LEVERS	TRP EVO Expert
CASSETTE	SRAM GX XS-1270 Eagle Transmission 10-52T
CHAIN	KMC eFlatHT
CRANKSET	Praxis e-HD alloy crank arms SRAM Eagle Transmission steel direct mount, 36T chain ring S:155mm, M: 155mm, L:155mm, XL:155mm
BOTTOM BRACKET	N/A

WHEELS	
RIMS	Giant E-TRA Hookless Tubeless ready Alloy 29" [F] 27.5" [R] 30mm inner width
HUBS	[F] Giant E-TRA MTB Alloy Hub, 6 Bolt, 28H [R] Giant E-TRA MTB Alloy Hub, HG Drive Body 72T Helical-Bevel Ratchet Driver, 6 Bolt, 28H
SPOKES	Sapim Laser, e-bike optimised
TYRES	Maxxis Assagai 29x2.5" foldable, Tubeless, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" foldable, Tubeless, EXO+ 3C Maxx Terra [R]
EXTRAS	Tyre Pressure Management System, Torx 25 Battery Lock with built-in Torque limiter, Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
FENDER/CHAINGUARD	Co-moulded guide 32-36T adjustable

Price: \$11,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Seat Tube Angle	76.6° 77.0° 77.4°			76.6° 77.0° 77.4°			76.6° 77.0° 77.4°			76.6° 77.0° 77.4°		
Top Tube Length (mm)	568 567 566			605 604 603			630 629 628			662 661 660		
Head Tube Length (mm)	110			120			130			140		
Head Tube Angle	64.1° 64.5° 64.9°			64.1° 64.5° 64.9°			64.1° 64.5° 64.9°			64.1° 64.5° 64.9°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	135.9			135.9			135.9			135.9		
Wheelbase (mm)	1200 1199 1197			1239 1237 1236			1267 1265 1264			1300 1299 1298		
Chain Stay Length (mm)	443 443 443			443 443 443			443 443 443			443 443 443		
Bottom Bracket Drop (mm)	17 12 7			17 12 7			17 12 7			17 12 7		
Stack (mm)	634 631 629			643 640 638			652 649 647			661 659 658		
Reach (mm)	422 425 428			457 460 463			477 480 484			504 510 513		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	155			155			155			155		
Wheel Size	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.