

TRANCE ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
CONTROLLER	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO Lux
BATTERY	EnergyPak 840Wh, 48V
CHARGER	48V 4A Smart Charger X
FRAME	
SIZES	S/M/L/XL
COLORS	Carbon/Tactical Grey, Dusted Peri
FRAME	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORK	Fox 36 Performance, 160mm travel, Grip damper
SHOCK	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPS	Giant Tactal Pro
STEM	Giant Contact SL Trail integrated, 40mm
SEATPOST	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SADDLE	Giant Romero SL HD
DRIVETRAIN	
SHIFTERS	Sram AXS Pod Rocker, discrete clamp
REAR DERAILLEUR	SRAM GX AXS
BRAKES	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BRAKE LEVERS	TRP EVO Expert
CASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
CHAIN	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
CRANKSET	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

WHEELS	
RIMS	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
HUBS	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPOKES	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
TIRES	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4"" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
FENDER/CHAINGUARD	Co-molded guide 32-36T adjustable

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Seat Tube Angle	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°
Top Tube Length (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Head Tube Length (mm)	110			120			130			140		
Head Tube Angle	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	135.9			135.9			135.9			135.9		
Wheelbase (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1298
Chain Stay Length (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Bottom Bracket Drop (mm)	17	12	7	17	12	7	17	12	7	17	12	7
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	658
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	155			155			155			155		
Wheel Size	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.