

TRANCE ADVANCED E+ 1



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
CONTROLLER	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO Lux
BATTERY	EnergyPak 840Wh, 48V
CHARGER	48V 4A Smart Charger X
FRAME	
SIZES	S/M/L/XL
FRAME	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORK	Fox 36 Performance, 160mm travel, Grip damper
SHOCK	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPS	Giant Tactal Pro
STEM	Giant Contact SL Trail integrated, 40mm
SEATPOST	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SADDLE	Giant Romero SL HD
DRIVETRAIN	
SHIFTERS	Sram AXS Pod Rocker, discrete clamp
REAR DERAILLEUR	SRAM GX AXS
BRAKES	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BRAKE LEVERS	TRP EVO Expert
CASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
CHAIN	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
CRANKSET	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

WHEELS	
RIMS	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
HUBS	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPOKES	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
TIRES	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
FENDER/CHAINGUARD	Co-molded guide 32-36T adjustable

Recommended Retail Price: \$8,000.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (inch)	15.7			16.7			17.7			18.7		
Seat Post Insertion Depth (inch)	9.6			10.6			11.6			12.2		
Seat Tube Angle	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°
Top Tube Length (inch)	22.4	22.3	22.3	23.8	23.8	23.7	24.8	24.8	24.7	26.1	26	26
Head Tube Length (inch)	4.3			4.7			5.1			5.5		
Head Tube Angle	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°
Fork Rake (inch)	1.7			1.7			1.7			1.7		
Trail (inch)	5.3			5.3			5.3			5.3		
Wheelbase (inch)	47.2	47.2	47.1	48.8	48.7	48.7	49.9	49.8	49.8	51.2	51.1	51.
Chain Stay Length (inch)	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.4	17.
Bottom Bracket Drop (inch)	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3
Stack (inch)	25	24.8	24.8	25.3	25.2	25.1	25.7	25.6	25.5	26	25.9	25.9
Reach (inch)	16.6	16.7	16.9	18	18.1	18.2	18.8	18.9	19.1	19.8	20.1	20.
Handlebar Width (inch)	31.5			31.5			31.5			31.5		
Stem Length (inch)	1.6			1.6			1.6			1.6		
Crank Length (inch)	6.1			6.1			6.1			6.1		
Wheel Size	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*