

TRANCE ADVANCED E+ 1



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
OHJAUSYKSIKKÖ	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
NÄYTTÖ	RideControl GO Lux
AKKU	EnergyPak 840Wh, 48V
LATURI	48V 4A Smart Charger X
RUNKO	
KOOT	S/M/L/XL
RUNKO	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
HAARUKKA	Fox 36 Performance, 160mm travel, Grip damper
ISKUNVAIMENNIN	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
KOMONENTIT	
OHJAUSTANKKO	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPIT	Giant Tactal Pro
OHJAINKANNATIN	Giant Contact SL Trail integrated, 40mm
SATULATOLPPA	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SATULA	Giant Romero SL HD
VOIMANSIIRTO	
VAIHDEVIPU	Sram AXS Pod Rocker, discrete clamp
TAKAVAIHTAJA	SRAM GX AXS
JARRUT	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
JARRUKAHVAT	TRP EVO Expert
RATASPAKKA	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
KETJUT	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
KAMPISARJA	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

RENKAAT	
VANTEET	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
NAVAT	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
PINNAT	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
RENKAAT	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
LISÄTIEDOT	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
TARVIKKEET	
KETJUNSUOJA	Co-molded guide 32-36T adjustable

Suositus hinta: 8 499,00 €

GEOMETRIA

RUNKO	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Satulaputken pituus (mm)	400	425	450	475
Satulatolpan asennussyvyys (mm)	245	270	295	310
Satulaputken kulma	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°
Vaakaputken pituus (mm)	568 567 566	605 604 603	630 629 628	662 661
Emäputken pituus (mm)	110	120	130	140
Emäputken kulma	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	135,9	135,9	135,9	135,9
Akseliväli (mm)	1200 1199 1197	1239 1237 1236	1267 1265 1264	1300 1299 1298
Takahaarukan alaputken pituus (mm)	443 443 443	443 443 443	443 443 443	443 443
Keskiön pudotus (mm)	17 12 7	17 12 7	17 12 7	17 12 7
Stack-mitta (mm)	634 631 629	643 640 638	652 649 647	661 659
Reach-mitta (mm)	422 425 428	457 460 463	477 480 484	504 510
Ohjaustangon leveys (mm)	800	800	800	800
Ohjainkannattimen pituus (mm)	40	40	40	40
Kammen pituus (mm)	155	155	155	155
Rengaskoko	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.