

TRANCE ADVANCED E+ 1



FELSZERELTSÉG

HIBRID KERÉKPÁR TECHNOLÓGIA	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
KEZELŐ	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
KIJELZŐ	RideControl GO Lux
AKKUMULÁTOR	EnergyPak 840Wh, 48V
TÖLTŐ	48V 4A Smart Charger X
VÁZ	
MÉRETEK	S/M/L/XL
VÁZ	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
VILLA	Fox 36 Performance, 160mm travel, Grip damper
RUGÓSTAG	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
ALKATRÉSZEK	
KORMÁNY	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
MARKOLAT	Giant Tactal Pro
KORMÁNSZÁR	Giant Contact SL Trail integrated, 40mm
NYEREGCSŐ	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
NYEREG	Giant Romero SL HD
HAJTÁS	
VÁLTÓKAROK	Sram AXS Pod Rocker, discrete clamp
HÁTSÓ VÁLTÓ	SRAM GX AXS
FÉKEK	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
FÉKKAROK	TRP EVO Expert
FOGASKOSZORÚ	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
LÁNC	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
HAJTÓMŰ	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

KEREKEK	
FELNIK	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
AGYAK	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
KÜLLÖK	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
KÜLSŐK	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
KIEGÉSZÍTŐK	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
KIEGÉSZÍTŐK	
SÁRVÉDŐ/LÁNCVÉDŐ	Co-molded guide 32-36T adjustable

Ár: 3 099 900,00 Ft

GEOMETRIA

VÁZ	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Nyeregcső hossz (mm)	400			425			450			475
Ülésoszlop behelyezési mélysége (mm)	245			270			295			310
Nyeregcső szög	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°
Felsőcső hossz (mm)	568	567	566	605	604	603	630	629	628	662
Fejcső hossz (mm)	110			120			130			140
Fejcsőszög	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°
Fork Rake (mm)	44			44			44			44
Trail (mm)	135,9			135,9			135,9			135,9
Keréktávolság (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300
Láncvilla hossz (mm)	443	443	443	443	443	443	443	443	443	443
Középcsapágy esés (mm)	17	12	7	17	12	7	17	12	7	17
Stack (mm)	634	631	629	643	640	638	652	649	647	661
Reach (mm)	422	425	428	457	460	463	477	480	484	504
Kormányzélesség (mm)	800			800			800			800
Kormányszár hossz (mm)	40			40			40			40
Hajtókar hossz (mm)	155			155			155			155
Kerékméret	29" [F], 27,5" [R]			29" [F], 27,5" [R]			29" [F], 27,5" [R]			29" [F], 2

A felsorolt leírások előzetes értesítés nélkül is változhatnak.