

TRANCE ADVANCED E+ 1



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
BEDIENINGSUNIT	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
DISPLAY	RideControl GO Lux
ACCU	EnergyPak 840Wh, 48V
LADER	48V 4A Smart Charger X
FRAME	
MATEN	S/M/L/XL
FRAME	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
VOORVORK	Fox 36 Performance, 160mm travel, Grip damper
DEMPER	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
ONDERDELEN	
STUUR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
HANDVATTEN	Giant Tactal Pro
STUURPEN	Giant Contact SL Trail integrated, 40mm
ZADEL PEN	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
ZADEL	Giant Romero SL HD
AFMONTAGE	
SHIFTERS	Sram AXS Pod Rocker, discrete clamp
ACHTTERDERAILLEUR	SRAM GX AXS
REMMEN	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
REMHENDELS	TRP EVO Expert
CASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
AANDRIJVING	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
CRANKSET	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

WIELSET	
VELGEN	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
NAVEN	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPAKEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
BANDEN	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRA'S	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
SPATBORD/ KETTINGKAST	Co-molded guide 32-36T adjustable

Adviesprijs: € 7.999,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW MID HIGH	LOW MID HIGH			LOW MID HIGH			LOW MID H				
Zitbuis lengte (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Zitbuis hoek	76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°		
Frame Lengte (horizontaal) (mm)	568 567 566	605 604 603			630 629 628			662 661 660				
Balhoofdbuis Lengte (mm)	110			120			130			140		
Balhoofdbuis Hoek	64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°		
Vork Sprong (mm)	44			44			44			44		
Naloop (mm)	135,9			135,9			135,9			135,9		
Wielbasis (mm)	1200 1199 1197	1239 1237 1236			1267 1265 1264			1300 1299 1298				
Liggende achtervork lengte (mm)	443 443 443	443 443 443			443 443 443			443 443 443				
Bottom Bracket Drop (mm)	17 12 7	17 12 7			17 12 7			17 12 7				
Stack (mm)	634 631 629	643 640 638			652 649 647			661 659 656				
Reach (mm)	422 425 428	457 460 463			477 480 484			504 510 513				
Stuur breedte (mm)	800			800			800			800		
Stuurpen Lengte (mm)	40			40			40			40		
Cranklengte (mm)	155			155			155			155		
Wielmaat	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.