

TRANCE ADVANCED E+ 1



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
SENSOR	RideControl Ergo 5 wireless Integrated E+ System & seatpost remote
ECRÃ	RideControl GO Lux
BATERIA	EnergyPak 840Wh, 48V
CARREGADOR	48V 4A Smart Charger X
QUADRO	
TAMANHOS	S/M/L/XL
QUADRO	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORQUILHA	Fox 36 Performance, 160mm travel, Grip damper
AMORTECEDORES	Fox Float X, Performance 2-position, 185x55mm Custom Tuned. Recommended sag: 30%
COMPONENTES	
GUIADOR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
PUNHOS	Giant Tactal Pro
AVANÇO	Giant Contact SL Trail integrated, 40mm
ESPIGÃO DE SELIM	Giant Contact Switch E+, 30.9mm electronic travel-adjust dropper post, (S:140, M-L:170, XL:200)
SELIM	Giant Romero SL HD
TRANSMISSÃO	
MANETES	Sram AXS Pod Rocker, discrete clamp
DESVIADOR TRASEIRO	SRAM GX AXS
TRAVÕES	TRP EVO Expert, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
MANÍPULOS DOS TRAVÕES	TRP EVO Expert
CASSETTE	SRAM Eagle Transmission, XS-1270, 10-52T, 12-speed
CORRENTE	KMC eFlatHT, high-torque e-bike optimized flat-top chain 12-speed
CONJUNTO PEDALEIRO	Praxis TYPE-2 alloy, SRAM Eagle Transmission 104BCD 36T

RODAS	
AROS	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
CUBOS	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RAIOS	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
PNEUS	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACESSÓRIOS	
GUARDA LAMAS/PROTECTOR DE CORRENTE	Co-molded guide 32-36T adjustable

Preço: 7 049,00 €

GEOMETRIA

QUADRO	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Comprimento do tubo do assento (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Ângulo do tubo do assento	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°
Comprimento do tubo superior (mm)	568 567 566	605 604 603	630 629 628	662 661 660								
Comprimento do tubo principal (mm)	110			120			130			140		
Ângulo do tubo principal	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°
Garfo ancinho (mm)	44			44			44			44		
Trilha (mm)	135,9			135,9			135,9			135,9		
distância entre eixos (mm)	1200 1199 1197	1239 1237 1236	1267 1265 1264	1300 1299 1298								
Comprimento Chain Stay (mm)	443 443 443	443 443 443	443 443 443	443 443 443								
Suporte inferior (mm)	17 12 7	17 12 7	17 12 7	17 12 7								
Pilha (mm)	634 631 629	643 640 638	652 649 647	661 658 656								
Alcançar (mm)	422 425 428	457 460 463	477 480 484	504 507 510								
Largura do guidão (mm)	800			800			800			800		
Comprimento da haste (mm)	40			40			40			40		
Comprimento da Manivela (mm)	155			155			155			155		
Tamanho da roda	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]	29" [F], 27.5" [R]								

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.