

TRANCE ADVANCED E+ 2



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
MANDO	RideControl Ergo 4
PANTALLA	RideControl GO Lux
BATERÍA	EnergyPak 840Wh, 48V
CARGADOR	48V 4A Smart Charger X
CUADRO	
TALLAS	S/M/L/XL
CUADRO	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
HORQUILLA	Rock Shox Psylo Gold RC, 160mm travel, Isolator RC damper, 15x110 Boost Maxle Stealth axle
AMORTIGUADOR	Rock Shox Deluxe Select, 185x55mm, Custom Tuned, Recommended sag: 30%
COMPONENTES	
MANILLAR	Giant Contact TR35, 35mm rise, Up: 5° Back: 9°, 35x800mm
PUÑOS	Giant Tactal Pro
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Giant Contact Switch AT, 30.9mm travel-adjust dropper post, (S:140, M:170, L-XL:200)
SILLÍN	Giant Romero HD
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore 12-speed
CAMBIO TRASERO	Shimano Deore, 12-speed shadow+
FRENOS	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
PALANCAS DE FRENOS	TRP EVO Comp
CASETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
CADENA	KMC e12HT, high-torque e-bike optimized chain 12-speed
JGO. PLATOS Y BIELAS	Praxis TYPE-2 alloy, Praxis 36T

RUEDAS	
LLANTAS	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
BUJES	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RADIOS	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
CUBIERTAS	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
GUARDABARROS/CUBRE-CADENA	Co-molded guide 32-36T adjustable

Precio: 5.999,00 €

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	245			270			295			310
Ángulo del tubo del sillín	76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6°
Longitud del tubo superior (mm) (mm)	568	567	566	605	604	603	630	629	628	662
Longitud del tubo de dirección (mm) (mm)	110			120			130			140
Ángulo del tubo de dirección	64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	135,9			135,9			135,9			135,9
Distancia entre ejes (mm) (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300
Longitud de la vaina (mm) (mm)	443	443	443	443	443	443	443	443	443	443
Caída del eje de pedalier (mm) (mm)	17	12	7	17	12	7	17	12	7	17
Stack (mm) (mm)	634	631	629	643	640	638	652	649	647	661
Reach (mm) (mm)	422	425	428	457	460	463	477	480	484	504
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			40			40
Longitud de las bielas (mm) (mm)	155			155			155			155
Tamaño de ruedas	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.