

TRANCE ADVANCED E+ 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
CONTROLLER	RideControl Ergo 4
DISPLAY	RideControl GO Lux
BATTERY	EnergyPak 840Wh, 48V
CHARGER	48V 4A Smart Charger X
FRAME	
SIZES	S/M/L/XL
FRAME	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORK	Rock Shox Psylo Gold RC, 160mm travel, Isolator RC damper, 15x110 Boost Maxle Stealth axle
SHOCK	Rock Shox Deluxe Select, 185x55mm, Custom Tuned, Recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 35mm rise, Up: 5° Back: 9°, 35x800mm
GRIPS	Giant Tactal Pro
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch AT, 30.9mm travel-adjust dropper post, (S:140, M:170, L-XL:200)
SADDLE	Giant Romero HD
DRIVETRAIN	
SHIFTERS	Shimano Deore 12-speed
REAR DERAILLEUR	Shimano Deore, 12-speed shadow+
BRAKES	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
BRAKE LEVERS	TRP EVO Comp
CASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
CHAIN	KMC e12HT, high-torque e-bike optimized chain 12-speed
CRANKSET	Praxis TYPE-2 alloy, Praxis 36T

WHEELS	
RIMS	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
HUBS	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPOKES	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
TIRES	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
FENDER/CHAINGUARD	Co-molded guide 32-36T adjustable

Suggested Retail Price (CDN): \$8,299.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Seat Tube Angle	76.6° 77.0° 77.4°			76.6° 77.0° 77.4°			76.6° 77.0° 77.4°			76.6° 77.0° 77.4°		
Top Tube Length (mm)	568 567 566			605 604 603			630 629 628			662 661 660		
Head Tube Length (mm)	110			120			130			140		
Head Tube Angle	64.1° 64.5° 64.9°			64.1° 64.5° 64.9°			64.1° 64.5° 64.9°			64.1° 64.5° 64.9°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	135.9			135.9			135.9			135.9		
Wheelbase (mm)	1200 1199 1197			1239 1237 1236			1267 1265 1264			1300 1299 1298		
Chain Stay Length (mm)	443 443 443			443 443 443			443 443 443			443 443 443		
Bottom Bracket Drop (mm)	17 12 7			17 12 7			17 12 7			17 12 7		
Stack (mm)	634 631 629			643 640 638			652 649 647			661 659 658		
Reach (mm)	422 425 428			457 460 463			477 480 484			504 510 513		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			40			40		
Crank Length (mm)	155			155			155			155		
Wheel Size	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

All prices and specifications are subject to change without notice.