

# TRANCE ADVANCED E+ 2



## TECHNIQUES

| TECHNOLOGIE HYBRID         |                                                                                                                                                                                                             |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MOTEUR                     | SyncDrive Pro4, 120Nm, 48V, 850W Peak Power                                                                                                                                                                 |
| COMMANDE                   | RideControl Ergo 4                                                                                                                                                                                          |
| ECRAN                      | RideControl GO Lux                                                                                                                                                                                          |
| BATTERIE                   | EnergyPak 840Wh, 48V                                                                                                                                                                                        |
| ENERGYPAK PLUS COMPATIBLES | EnergyPakPlus 280Wh                                                                                                                                                                                         |
| CHARGEUR                   | 48V 4A Smart Charger X                                                                                                                                                                                      |
| CONNECTIVITÉ               | E-Lock, FindMyBike, Tire Checker Aegis                                                                                                                                                                      |
| CADRE                      |                                                                                                                                                                                                             |
| TAILLES                    | S, M, L, XL                                                                                                                                                                                                 |
| COLORIS                    | FanaticTeal/DeepLake, Moon Dust/Carbon                                                                                                                                                                      |
| CADRE                      | Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible |
| FOURCHE                    | Rock Shox Psylo Gold RC, 160mm travel, Isolator RC damper, 15x110 Boost Maxle Stealth axle                                                                                                                  |
| AMORTISSEUR                | Rock Shox Deluxe Select, 185x55mm, Custom Tuned, Recommended sag: 30%                                                                                                                                       |
| COMPOSANTS                 |                                                                                                                                                                                                             |
| CINTRE                     | Giant Contact TR35, 35mm rise, Up: 5° Back: 9°, 35x800mm                                                                                                                                                    |
| POIGNÉES                   | Giant Tactal Pro                                                                                                                                                                                            |
| POTENCE                    | Giant Contact SL 35                                                                                                                                                                                         |
| TIGE DE SELLE              | Giant Contact Switch AT, 30.9mm travel-adjust dropper post, (S:140, M:170, L:XL:200)                                                                                                                        |
| SELLE                      | Giant Romero HD                                                                                                                                                                                             |
| DÉRAILLEUR                 |                                                                                                                                                                                                             |
| MANETTES                   | Shimano Deore 12-speed                                                                                                                                                                                      |
| DÉRAILLEUR ARRIÈRE         | Shimano Deore, 12-speed shadow+                                                                                                                                                                             |
| FREINS                     | TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F] 203mm [R]                                                                                                                                                 |
| LEVIER DE FREIN            | TRP EVO Comp                                                                                                                                                                                                |
| CASSETTE                   | Shimano Deore, HyperGlide+, 12-speed, 11-51T                                                                                                                                                                |
| CHAÎNE                     | KMC e12HT, high-torque e-bike optimized chain 12-speed                                                                                                                                                      |
| PÉDALIER                   | Praxis TYPE-2 alloy, Praxis 36T                                                                                                                                                                             |

| ROUES               |                                                                                                                                 |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------|
| JANTES              | Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology                                                                     |
| MOYEUX              | Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized               |
| RAYONS              | Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)                                                                                  |
| PNEUS               | Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R] |
| EXTRAS              | Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)   |
| ACCESSOIRES         |                                                                                                                                 |
| GARDE-BOUE / CHAÎNE | Co-molded guide 32-36T adjustable                                                                                               |

Prix Public Conseillé: 6 000,00 €

## GÉOMÉTRIE

| CADRE                              | S                  |       |       | M                  |       |       | L                  |       |       | XL                 |       |       |
|------------------------------------|--------------------|-------|-------|--------------------|-------|-------|--------------------|-------|-------|--------------------|-------|-------|
|                                    | LOW                | MID   | HIGH  | LOW                | MID   | HIGH  | LOW                | MID   | HIGH  | LOW                | MID   | HIGH  |
| Longueur de tube de selle (mm)     | 400                |       |       | 425                |       |       | 450                |       |       | 475                |       |       |
| Seat Post Insertion Depth (mm)     | 245                |       |       | 270                |       |       | 295                |       |       | 310                |       |       |
| Angle de tube de selle             | 76,6°              | 77,0° | 77,4° | 76,6°              | 77,0° | 77,4° | 76,6°              | 77,0° | 77,4° | 76,6°              | 77,0° | 77,4° |
| Longueur du tube supérieur (mm)    | 568                | 567   | 566   | 605                | 604   | 603   | 630                | 629   | 628   | 662                | 661   | 660   |
| Longueur du tube de direction (mm) | 110                |       |       | 120                |       |       | 130                |       |       | 140                |       |       |
| Angle du tube de direction         | 64,1°              | 64,5° | 64,9° | 64,1°              | 64,5° | 64,9° | 64,1°              | 64,5° | 64,9° | 64,1°              | 64,5° | 64,9° |
| Déport de fourche (mm)             | 44                 |       |       | 44                 |       |       | 44                 |       |       | 44                 |       |       |
| Trail (mm)                         | 135,9              |       |       | 135,9              |       |       | 135,9              |       |       | 135,9              |       |       |
| Empattement (mm)                   | 1200               | 1199  | 1197  | 1239               | 1237  | 1236  | 1267               | 1265  | 1264  | 1300               | 1299  | 1297  |
| Longueur des bases (mm)            | 443                | 443   | 443   | 443                | 443   | 443   | 443                | 443   | 443   | 443                | 443   | 443   |
| Drop du boîtier de pédalier (mm)   | 17                 | 12    | 7     | 17                 | 12    | 7     | 17                 | 12    | 7     | 17                 | 12    | 7     |
| Stack (mm)                         | 634                | 631   | 629   | 643                | 640   | 638   | 652                | 649   | 647   | 661                | 659   | 657   |
| Reach (mm)                         | 422                | 425   | 428   | 457                | 460   | 463   | 477                | 480   | 484   | 504                | 510   | 515   |
| Largeur de cintre (mm)             | 800                |       |       | 800                |       |       | 800                |       |       | 800                |       |       |
| Longueur de potence (mm)           | 40                 |       |       | 40                 |       |       | 40                 |       |       | 40                 |       |       |
| Longueur des manivelles (mm)       | 155                |       |       | 155                |       |       | 155                |       |       | 155                |       |       |
| Diamètre des roues                 | 29" [F], 27.5" [R] |       |       | 29" [F], 27.5" [R] |       |       | 29" [F], 27.5" [R] |       |       | 29" [F], 27.5" [R] |       |       |

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).  
GIANT France se réserve le droit de modifier les spécifications sans préavis.