

TRANCE ADVANCED E+ 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
COMANDO	RideControl Ergo 4
DISPLAY	RideControl GO Lux
BATTERIA	EnergyPak 840Wh, 48V
CARICATORE	48V 4A Smart Charger X
TELAIO	
TAGLIE	S/M/L/XL
TELAIO	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
FORCELLA	Rock Shox Psylo Gold RC, 160mm travel, Isolator RC damper, 15x110 Boost Maxle Stealth axle
AMMORTIZZATORE	Rock Shox Deluxe Select, 185x55mm, Custom Tuned, Recommended sag: 30%
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, 35mm rize, Up: 5° Back: 9°, 35x800mm
MANOPOLE	Giant Tactal Pro
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISSELLA	Giant Contact Switch AT, 30.9mm travel-adjust dropper post, (S:140, M:170, L-XL:200)
SELLA	Giant Romero HD
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore 12-speed
DERAGLIATORE POSTERIORE	Shimano Deore, 12-speed shadow+
FRENI	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
COMANDI FRENO	TRP EVO Comp
PACCO PIGNONI	Shimano Deore, HyperGlide+, 12-speed, 11-51T
CATENA	KMC e12HT, high-torque e-bike optimized chain 12-speed
GUARNITURA	Praxis TYPE-2 alloy, Praxis 36T

RUOTE	
CERCHI	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
MOZZI	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
RAGGI	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
COPERTONI	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRA	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
PARAFANGO / PARACATENA	Co-molded guide 32-36T adjustable

Prezzo: 5.999,00 €

GEOMETRIA

TELAIO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Lunghezza Tubo Sella (mm)	400			425			450			475
Profondità inserimento reggisella (mm)	245			270			295			310
Angolo Tubo Sella	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°
Lunghezza Tubo Orizzontale (mm)	568	567	566	605	604	603	630	629	628	662
Lunghezza Tubo Sterzo (mm)	110			120			130			140
Angolo Sterzo	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°
Rake Forcella (mm)	44			44			44			44
Avancorsa (mm)	135,9			135,9			135,9			135,9
Interasse (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300
Lunghezza Carro Posteriore (mm)	443	443	443	443	443	443	443	443	443	443
Drop Movimento Centrale (mm)	17	12	7	17	12	7	17	12	7	17
Stack (mm)	634	631	629	643	640	638	652	649	647	661
Reach (mm)	422	425	428	457	460	463	477	480	484	504
Larghezza Manubrio c/c (mm)	800			800			800			800
Lunghezza Attacco Manubrio (mm)	40			40			40			40
Lunghezza Pedivella (mm)	155			155			155			155
Dimensione Ruote	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 2

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.