

TRANCE ADVANCED E+ 2



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro4, 120Nm, 48V, 850W Peak Power
BEDIENINGSUNIT	RideControl Ergo 4
DISPLAY	RideControl GO Lux
ACCU	EnergyPak 840Wh, 48V
LADER	48V 4A Smart Charger X
FRAME	
MATEN	S/M/L/XL
FRAME	Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible
VOORVORK	Rock Shox Psylo Gold RC, 160mm travel, Isolator RC damper, 15x110 Boost Maxle Stealth axle
DEMPER	Rock Shox Deluxe Select, 185x55mm, Custom Tuned, Recommended sag: 30%
ONDERDELEN	
STUUR	Giant Contact TR35, 35mm rise, Up: 5° Back: 9°, 35x800mm
HANDVATTEN	Giant Tactal Pro
STUURPEN	Giant Contact SL 35
ZADELPEN	Giant Contact Switch AT, 30.9mm travel-adjust dropper post, (S:140, M:170, L-XL:200)
ZADEL	Giant Romero HD
AFMONTAGE	
SHIFTERS	Shimano Deore 12-speed
ACHTERDERAILLEUR	Shimano Deore, 12-speed shadow+
REMMEN	TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F] 203mm [R]
REMHENDELS	TRP EVO Comp
CASSETTE	Shimano Deore, HyperGlide+, 12-speed, 11-51T
AANDRIJVING	KMC e12HT, high-torque e-bike optimized chain 12-speed
CRANKSET	Praxis TYPE-2 alloy, Praxis 36T

WIELSET	
VELGEN	Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology
NAVEN	Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized
SPAKEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
BANDEN	Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R]
EXTRA'S	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
SPATBORD/ KETTINGKAST	Co-molded guide 32-36T adjustable

Adviesprijs: € 5.999,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW MID HIGH	LOW MID HIGH			LOW MID HIGH			LOW MID H				
Zitbuis lengte (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	245			270			295			310		
Zitbuis hoek	76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°		
Frame Lengte (horizontaal) (mm)	568 567 566	605 604 603			630 629 628			662 661 660				
Balhoofdbuis Lengte (mm)	110			120			130			140		
Balhoofdbuis Hoek	64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°		
Vork Sprong (mm)	44			44			44			44		
Naloop (mm)	135,9			135,9			135,9			135,9		
Wielbasis (mm)	1200 1199 1197	1239 1237 1236			1267 1265 1264			1300 1299 1297				
Liggende achtervork lengte (mm)	443 443 443	443 443 443			443 443 443			443 443 443				
Bottom Bracket Drop (mm)	17 12 7	17 12 7			17 12 7			17 12 7				
Stack (mm)	634 631 629	643 640 638			652 649 647			661 659 656				
Reach (mm)	422 425 428	457 460 463			477 480 484			504 510 513				
Stuur breedte (mm)	800			800			800			800		
Stuurpen Lengte (mm)	40			40			40			40		
Cranklengte (mm)	155			155			155			155		
Wielmaat	29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]			29" [F], 27.5" [R]		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.