

# TRANCE ADVANCED E+ 2



## SPECS

| HYBRID CYKELTEKNIK |                                                                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MOTOR              | SyncDrive Pro4, 120Nm, 48V, 850W Peak Power                                                                                                                                                                 |
| KONTROLLER         | RideControl Ergo 4                                                                                                                                                                                          |
| VISA               | RideControl GO Lux                                                                                                                                                                                          |
| BATTERI            | EnergyPak 840Wh, 48V                                                                                                                                                                                        |
| LADDARE            | 48V 4A Smart Charger X                                                                                                                                                                                      |
| RAM                |                                                                                                                                                                                                             |
| STORLEKAR          | S/M/L/XL                                                                                                                                                                                                    |
| RAM                | Advanced SL-grade composite frame, Advanced forged composite upper rocker, 150mm Maestro suspension system, 3-position Flip-Chip adjustable geometry, 148mm Boost hub spacing, ZS66/ZS66 Headset compatible |
| GAFFEL             | Rock Shox Psylo Gold RC, 160mm travel, Isolator RC damper, 15x110 Boost Maxle Stealth axle                                                                                                                  |
| BAKDÄMPARE         | Rock Shox Deluxe Select, 185x55mm, Custom Tuned, Recommended sag: 30%                                                                                                                                       |
| KOMPONENTER        |                                                                                                                                                                                                             |
| STYRE              | Giant Contact TR35, 35mm rize, Up: 5° Back: 9°, 35x800mm                                                                                                                                                    |
| GREPPAR            | Giant Tactal Pro                                                                                                                                                                                            |
| STAM               | Giant Contact SL 35                                                                                                                                                                                         |
| SADELSTOLPE        | Giant Contact Switch AT, 30.9mm travel-adjust dropper post, (S:140, M:170, L-XL:200)                                                                                                                        |
| SADEL              | Giant Romero HD                                                                                                                                                                                             |
| DRIVLINAN          |                                                                                                                                                                                                             |
| VÄXLAR             | Shimano Deore 12-speed                                                                                                                                                                                      |
| BAKVÄXEL           | Shimano Deore, 12-speed shadow+                                                                                                                                                                             |
| BROMSAR            | TRP EVO Comp, hydraulic disc, 4-piston, 220mm [F] 203mm [R]                                                                                                                                                 |
| BROMSSPAKAR        | TRP EVO Comp                                                                                                                                                                                                |
| KASSETT            | Shimano Deore, HyperGlide+, 12-speed, 11-51T                                                                                                                                                                |
| KEDJA              | KMC e12HT, high-torque e-bike optimized chain 12-speed                                                                                                                                                      |
| VEVPARTI           | Praxis TYPE-2 alloy, Praxis 36T                                                                                                                                                                             |

| HJUL                  |                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------|
| FÄLGAR                | Giant TRA HD, Alloy, 30mm inner width, WideGuard Technology                                                                     |
| NAV                   | Giant TRA HD, E-Drive 350Nm, Titanium ratchet system, 72T engagement, 15x110mm [F] 12x148mm [R], e-bike optimized               |
| EKRAR                 | Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)                                                                                  |
| DÄCK                  | Maxxis Assagai 29X2.50" Foldable, TLR, EXO+, 3C Maxx Grip [F] Maxxis Minion DHR II 27.5x2.4" Foldable, TLR, EXO+, MaxxTerra [R] |
| EXTRAFUNKTIONER       | Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)   |
| TILLBEHÖR             |                                                                                                                                 |
| STÄNKSKÄRM/KEDJESKYDD | Co-molded guide 32-36T adjustable                                                                                               |

Price: 71 000,00 kr

## GEOMETRY

| RAM                            | S                     |     |      | M                     |     |      | L                     |     |      | XL                    |     |      |
|--------------------------------|-----------------------|-----|------|-----------------------|-----|------|-----------------------|-----|------|-----------------------|-----|------|
|                                | LOW                   | MID | HIGH | LOW                   | MID | HIGH | LOW                   | MID | HIGH | LOW                   | MID | HIGH |
| Längd sadelrör (mm)            | 400                   |     |      | 425                   |     |      | 450                   |     |      | 475                   |     |      |
| Seat Post Insertion Depth (mm) | 245                   |     |      | 270                   |     |      | 295                   |     |      | 310                   |     |      |
| Vinkel sadelrör                | 76,6°   77,0°   77,4° |     |      | 76,6°   77,0°   77,4° |     |      | 76,6°   77,0°   77,4° |     |      | 76,6°   77,0°   77,4° |     |      |
| Topprörets längd (mm)          | 568   567   566       |     |      | 605   604   603       |     |      | 630   629   628       |     |      | 662   661   660       |     |      |
| Styrhuvud Längd (mm)           | 110                   |     |      | 120                   |     |      | 130                   |     |      | 140                   |     |      |
| Vinkel styrhuvud               | 64,1°   64,5°   64,9° |     |      | 64,1°   64,5°   64,9° |     |      | 64,1°   64,5°   64,9° |     |      | 64,1°   64,5°   64,9° |     |      |
| Gaffelvinkel (mm)              | 44                    |     |      | 44                    |     |      | 44                    |     |      | 44                    |     |      |
| Spår (mm)                      | 135,9                 |     |      | 135,9                 |     |      | 135,9                 |     |      | 135,9                 |     |      |
| Hjulbas (mm)                   | 1200   1199   1197    |     |      | 1239   1237   1236    |     |      | 1267   1265   1264    |     |      | 1300   1299   1298    |     |      |
| Kedjestagslängd (mm)           | 443   443   443       |     |      | 443   443   443       |     |      | 443   443   443       |     |      | 443   443   443       |     |      |
| Nedre fäste Drop (mm)          | 17   12   7           |     |      | 17   12   7           |     |      | 17   12   7           |     |      | 17   12   7           |     |      |
| Stack (mm)                     | 634   631   629       |     |      | 643   640   638       |     |      | 652   649   647       |     |      | 661   659   658       |     |      |
| Reach (mm)                     | 422   425   428       |     |      | 457   460   463       |     |      | 477   480   484       |     |      | 504   510   513       |     |      |
| Styrets bredd (mm)             | 800                   |     |      | 800                   |     |      | 800                   |     |      | 800                   |     |      |
| Stamlängd (mm)                 | 40                    |     |      | 40                    |     |      | 40                    |     |      | 40                    |     |      |
| Vevlängd (mm)                  | 155                   |     |      | 155                   |     |      | 155                   |     |      | 155                   |     |      |
| Hjulstorlek                    | 29" [F], 27.5" [R]    |     |      | 29" [F], 27.5" [R]    |     |      | 29" [F], 27.5" [R]    |     |      | 29" [F], 27.5" [R]    |     |      |

All specifications listed are subject to change without notice.