

TRANCE ADVANCED E+ SE



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
KONTROLLER	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
DISPLAY	Giant RideControl Go Lux
BATTERI	Giant EnergyPak Smart 840, 48V
LADER	Giant Smart Charger X, 48 V 4A
RAMME	
RAMME	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
FORGAFFEL	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
BAGDÆMPER	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
KOMPONENTER	
STYR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GREB / STYRBÅND	Giant Tactal Pro
FREMPIND	Giant Contact SL Trail Integrated, 40 mm
SADELPIND	Giant Contact Switch E+, 30.9 mm, electronic dropper post
SADEL	Giant Romero HD
GEARGRUPPE	
SKIFTEGREB	Giant RideControl Ergo 5 wireless
BAGSKIFTER	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
BREMSE	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
BREMSEGREB	TRP EVO Comp
KASSETTE	Shimano LinkGlide, 11-speed, 11-50T
KÆDE	KMC eGlide, high-torque e-bike optimized chain 11-speed
KRANKSÆT	Praxis Type-2 alloy, 155 mm

HJUL	
FÆLGE	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
NAV	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
EGER	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
DÆK	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EKSTRA	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
TILBEHØR	
LYGTER	Optional: Giant Recon series e-bike lights available and direct-connect compatible
GRÆNSER	
KOMBINERET MAKSIMAL BELASTNINGSGRÆNSE	156kg

Pris: 51.609,00 kr.

GEOMETRI

RAMME	S			M			L			XL		
	LOW HIGH			LOW HIGH			LOW HIGH			LOW HIGH		
Sadelrøsvinkel	76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°		
Overrørslængde (mm)	568 567 566	605 604 603			630 629 628			662 661 660				
Kronrørslængde (mm)	110			120			130			140		
Kronrøsvinkel	64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°		
Akselafstand (mm)	1200 1199 1197			1239 1237 1236			1267 1265 1264			1300 1299 1298		
Kædestagslængde (mm)	443 443 443	443 443 443			443 443 443			443 443 443				
Stack (mm)	634 631 629	643 640 638			652 649 647			661 659 658				
Reach (mm)	422 425 428	457 460 463			477 480 484			504 510 513				
Pedalarmslængde (mm)	155			155			155			155		

Alle de anførte specifikationer kan ændres uden varsel.