

TRANCE ADVANCED E+ SE

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
CONTROLLER	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
DISPLAY	Giant RideControl Go Lux
BATTERY	Giant EnergyPak Smart 840, 48V
CHARGER	Giant Smart Charger X, 48 V 4A
FRAME	
FRAME	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
FORK	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
SHOCK	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
COMPONENTS	
HANDLEBAR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPS	Giant Tactal Pro
STEM	Giant Contact SL Trail Integrated, 40 mm
SEATPOST	Giant Contact Switch E+, 30.9 mm, electronic dropper post
SADDLE	Giant Romero HD
DRIVETRAIN	
SHIFTERS	Giant RideControl Ergo 5 wireless
REAR DERAILLEUR	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
BRAKES	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
BRAKE LEVERS	TRP EVO Comp
CASSETTE	Shimano LinkGlide, 11-speed, 11-50T
CHAIN	KMC eGlide, high-torque e-bike optimized chain 11-speed
CRANKSET	Praxis Type-2 alloy, 155 mm

WHEELS	
RIMS	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
HUBS	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
SPOKES	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
TIRES	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Suggested Retail Price (CDN): \$9,299.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW HIGH			LOW HIGH			LOW HIGH			LOW HIGH		
Seat Tube Angle	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°	76.6°	77.0°	77.4°
Top Tube Length (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Head Tube Length (mm)	110			120			130			140		
Head Tube Angle	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°	64.1°	64.5°	64.9°
Wheelbase (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1298
Chain Stay Length (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	658
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Crank Length (mm)	155			155			155			155		

All prices and specifications are subject to change without notice.