

TRANCE ADVANCED E+ SE



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
CONTROLLER	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
DISPLAY	Giant RideControl Go Lux
BATTERY	Giant EnergyPak Smart 840, 48V
CHARGER	Giant Smart Charger X, 48 V 4A
FRAME	
SIZES	M, L, XL
COLORS	Copper Flow
FRAME	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
FORK	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
SHOCK	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
COMPONENTS	
HANDLEBAR	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPS	Giant Tactal Pro
STEM	Giant Contact SL Trail Integrated, 40 mm
SEATPOST	Giant Contact Switch E+, 30.9 mm, electronic dropper post
SADDLE	Giant Romero HD
DRIVETRAIN	
SHIFTERS	Giant RideControl Ergo 5 wireless
REAR DERAILLEUR	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
BRAKES	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
BRAKE LEVERS	TRP EVO Comp
CASSETTE	Shimano LinkGlide, 11-speed, 11-50T
CHAIN	KMC eGlide, high-torque e-bike optimized chain 11-speed
CRANKSET	Praxis Type-2 alloy, 155 mm

WHEELS	
RIMS	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
HUBS	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
SPOKES	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
TIRES	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAS	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Price: \$12,199.00

GEOMETRY

FRAME	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Angle	76.6° 77.0° 77.4°	76.6° 77.0° 77.4°	76.6° 77.0° 77.4°
Top Tube Length (mm)	605 604 603	630 629 628	662 661 660
Head Tube Length (mm)	120	130	140
Head Tube Angle	64.1° 64.5° 64.9°	64.1° 64.5° 64.9°	64.1° 64.5° 64.9°
Wheelbase (mm)	1239 1237 1236	1267 1265 1264	1300 1299 1298
Chain Stay Length (mm)	443 443 443	443 443 443	443 443 443
Stack (mm)	643 640 638	652 649 647	661 659 658
Reach (mm)	457 460 463	477 480 484	504 510 513
Crank Length (mm)	155	155	155

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.