

TRANCE ADVANCED E+ SE



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
OHJAUSYKSIKKÖ	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
NÄYTTÖ	Giant RideControl Go Lux
AKKU	Giant EnergyPak Smart 840, 48V
LATURI	Giant Smart Charger X, 48 V 4A
RUNKO	
RUNKO	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
HAARUKKA	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
ISKUNVAIMENNIN	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
KOMONENTIT	
OHJAUSTANKO	Giant Contact SL Trail Integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GRIPIT	Giant Tactal Pro
OHJAINKANNATIN	Giant Contact SL Trail Integrated, 40 mm
SATULATOLPPA	Giant Contact Switch E+, 30.9 mm, electronic dropper post
SATULA	Giant Romero HD
VOIMANSIIRTO	
VAIHDEVIPU	Giant RideControl Ergo 5 wireless
TAKAVAIHTAJA	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
JARRUT	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
JARRUKAHVAT	TRP EVO Comp
RATASPAKKA	Shimano LinkGlide, 11-speed, 11-50T
KETJUT	KMC eGlide, high-torque e-bike optimized chain 11-speed
KAMPISARJA	Praxis Type-2 alloy, 155 mm

RENKAAT	
VANTEET	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
NAVAT	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
PINNAT	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
RENKAAT	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
LISÄTIEDOT	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
TARVIKKEET	
VALOT	Optional: Giant Recon series e-bike lights available and direct-connect compatible
RAJOITTEET	
COMBINED MAXIMUM LOAD LIMIT	156kg

Suositusuhinta: 6 909,00 €

GEOMETRIA

RUNKO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Satulaputken kulma	76,6° 77,0°	77,4° 76,6°	77,0° 77,4°	76,6° 77,0°
Vaakaputken pituus (mm)	568 567 566	605 604 603	630 629 628	662 661
Emäputken pituus (mm)	110	120	130	140
Emäputken kulma	64,1° 64,5°	64,9° 64,1°	64,5° 64,9°	64,1° 64,5°
Akseliväli (mm)	1200 1199 1197	1239 1237 1236	1267 1265 1264	1300 1299 1298
Takahaarukan alaputken pituus (mm)	443 443 443	443 443 443	443 443 443	443 443
Stack-mitta (mm)	634 631 629	643 640 638	652 649 647	661 659
Reach-mitta (mm)	422 425 428	457 460 463	477 480 484	504 510
Kammen pituus (mm)	155	155	155	155

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.